

SPECIFICATIONS

| | |
|--------------------------------|--|
| Construction | Textured Loop Pattern |
| Yarn Content | Avalar [®] X Nylon with Puralex [®] |
| Dye Method | Solution/Space |
| Machine Gauge | 1/10 in (39.4 in./10 cm.) |
| Stitch Count | 10 S.P.I (39.4/10 cm.) |
| Finished Pile Thickness | .087 in. (2.2 mm.) |
| Average Density | 11,586 |
| Yarn Weight Tufted | 28 oz. /yd. ² (949 g./m. ²) |
| Primary Backing | Polypropylene |
| Secondary Backing | Woven Polypropylene with Post Consumer Recycled Content |
| Width | 12 feet (3.66 m) |
| Pattern Repeat | N/A |
| Total Recycled Content | 2.50% |

PERFORMANCE

| | |
|-------------------------------|---------------------------------|
| Static Control | Less Than 3.5 K.V. Step |
| Flame Resistance | Passes (DOC FF-1-70) |
| Flooring Radiant Panel | Class 1 (ASTM E-648) |
| Smoke Density | Less than 450 (ASTM E-662) |
| Soil Resistance | Commercial Anti-Soil Protection |
| CRI Green Label Plus | Certification #GLP7078 |

FIESTA!

style # 6FST

WARRANTIES

| | |
|---------------|---------------------------|
| Wear | 10 Year Limited Warranty |
| Stain | Lifetime Limited Warranty |
| Static | Lifetime Limited Warranty |

ADDITIONAL INFORMATION

| | |
|------------------------|---|
| Custom Colors | Contact Sales Representative |
| Backing Options | See iLoc [®] backings at www.cambridgecarpet.com |
| Additives | Puralex [®] is a refresher that is environmentally friendly and specially formulated to help purify the air. |
| Samples | 800 451 1250 |



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Cambridge[®]

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand