

SPECIFICATIONS

Construction	Patterned Scroll
Yarn Content	Antron Lumena [®] Solution Dyed Nylon
Dye Method	Solution
Machine Gauge	1/12 in (39.4/10 cm.)
Stitch Count	12.8 S.P.I (50.3/ 10 cm.)
Finished Pile Thickness	.121" (3.07 mm.)
Average Density	8,390
Yarn Weight Tufted	28 oz. /yd. ² (949 g./m. ²)
Primary Backing	Masterline [®] Woven Primary
Secondary Backing	Woven Polypropylene
Width	12 feet (3.66 m.)
Pattern Repeat	24" w x 19.5" l (30.5 cm. x49.5 cm.)
Total Recycled Content	2.50%

PERFORMANCE

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	DuraTech [®] Soil Resistant Treatment
CRI Green Label Plus	Certification # GLP7078

WARRANTIES

Wear	10 Year Limited Warranty
Antistatic	Limited Lifetime Warranty
Colorfastness /Light	10 Year Limited Warranty
Colorfastness / Atmospheric	
Contaminants	5 Year Limited Warranty
Stain	Limited Lifetime Warranty

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc [®] backings at www.cambridgecarpet.com
Coordinating Styles	Park Avenue
Samples	800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

Carpet Design[®] 2005 Beaulieu Group, LLC.

FINAL AUDITION

style # 6FNL

Cambridge[®]

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand