SPECIFICATIONS

Dye Method

Construction Patterned Scroll

Yarn Content Avalar® SDX Nylon with 25% Post

Industrial Recycled Content and Puralex®

Solution Dyed

 Machine Gauge
 1/12 in (47.2 in./10 cm.)

 Stitch Count
 10 S.P.I (39.4/ 10 cm.)

 Finished Pile Thickness
 .116 in. (2.95 mm)

Average Density 7,759

Yarn Weight Tufted 25 oz. /yd.² (847 g./m.²)

Primary Backing
Secondary Backing
Non Woven
Nexterra® with 85%

Post Consumer Recycled Content 24" x 24" (61 cm. x 61cm.).)

Total Recycled Content 61-65%

PERFORMANCE

Static ControlLess Than 3.5 K.V. StepFlame ResistancePasses (DOC FF-1-70)Flooring Radiant PanelClass 1 (ASTM E-648)Smoke DensityLess than 450 (ASTM E-662)Soil ResistanceCommercial Anti-Soil ProtectionCRI Green Label PlusCertification # GLP8595

WARRANTIES

Wear Lifetime Limited Warranty
Static Lifetime Warranty
Lifetime Warranty

Tuft Bind Lifetime Warranty
Edge Ravel Lifetime Warranty

Zippering Lifetime Warranty, not to zipper wet or dry

Pilling & Fuzzing Lifetime Warranty

Delamination Lifetime Warranty, under normal use

Dimensional Stability Lifetime Warranty

ADDITIONAL INFORMATION

Custom ColorsContact Sales RepresentativeBacking OptionsSee iLoc® backings at

www.cambridgecarpet.com

AdditivesPuralex[®] is a refresher that is environmentally friendly and

specially formulated to help purify the air.

the a

Samples 800 451 1250







Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

TIGHTROPE

style # 6TTRP



201 Princeton Boulevard P.O. Box 1110 Adairsville, GA 30103 800 451 1250

335 Roxton Street Acton Vale, Quebec Canada JOH 1A0 888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand