

# GROVEPARK

## SPECIFICATIONS

---

Style Number	9GRP
Construction	Tip Sheared Loop Pattern
Yarn Content	Avalar® SD Nylon
Dye Method	Solution
Machine Gauge	1/8 in. (31.5 col./10 cm.)
Stitch Count	14 S.P.I. (55.1/10 cm.)
Finished Pile Thickness	.200 in. (5.1 mm)
Average Density	5,400
Yarn Weight Tufted	30 oz./yd.2 (1017 g./m2)
Primary Backing	Polypropylene
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66m.)
Pattern Repeat	1.0" w x 1.13" l (2.54 cm. x 2.9 cm.)
Total Recycled Content	2.43%

## PERFORMANCE

---

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078

## WARRANTIES

---

Wear	10 Year Limited
Stain	Lifetime Limited Stain Removal
Static	Lifetime Limited Static Control
Colorfastness	Lifetime Limited Against Light & Atmospheric Contaminants

## ADDITIONAL INFORMATION

---

Custom Colors	Contact Mill Representative
Backing Options	See iLoc® backings at <a href="http://aquahospitalitycarpets.com">aquahospitalitycarpets.com</a>
Samples	800 451 1250



201 Princeton Blvd.  
P.O. Box 1110  
Adairsville, GA 30103

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
(888) 467-5075

**Aqua**  
HOSPITALITY CARPETS

Specifications are based on averages from manufacturing processes and may vary within normal industry Tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance

A Beaulieu Commercial Brand