

# ST. GERMAIN

## SPECIFICATIONS

Style Number	9SGM
Construction	Textured Loop Pattern
Yarn Content	Avalar® SD Nylon
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	14 S.P.I. (55.1/10 cm.)
Finished Pile Thickness	.135 in. (3.43 mm)
Average Density	8,533
Yarn Weight Tufted	32 oz./yd.2 (1085 g./m2)
Primary Backing	Polypropylene
Secondary Backing	Woven Polypropylene with Post Consumer Recycled Content
Width	12 feet (3.66m.)
Pattern Repeat	6.0" w x 6.5" l (15.2 cm. x 16.5 cm.)

## PERFORMANCE

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078

## WARRANTIES

Wear	10 Year Limited
Stain	Lifetime Limited Stain Removal
Static	Lifetime Limited Static Control
Colorfastness	Lifetime Limited Against Light & Atmospheric Contaminants

## ADDITIONAL INFORMATION

Custom Colors	Contact Mill Representative
Backing Options	See iLoc® backings at <a href="http://aquahospitalitycarpets.com">aquahospitalitycarpets.com</a>
Samples	800 451 1250



201 Princeton Blvd.  
P.O. Box 1110  
Adairsville, GA 30103

335 Roxton Street  
Acton Vale, Quebec  
Canada J0H 1A0  
(888) 467-5075

**Aqua**  
HOSPITALITY CARPETS

Specifications are based on averages from manufacturing processes and may vary within normal industry Tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance  
A Beaulieu Commercial Brand