

(Covered Escutcheon)

EATU21 (White porcelain handles and indices) **EATU16** (Deck Unions)

EATU22-K (Metal handles and indices)

EATU24-K (Black porcelain handles and metal indices)

EATU25-K (Oak handles and metal indices)


(Uncovered Escutcheon)

EATU31 (White porcelain handles and indices)

EATU32-K (Metal handles and indices)

EATU34-K (Black porcelain handles and metal indices)

EATU35-K (Oak handles and metal indices)



Notes:

- Inlet connection: $\frac{3}{4}$ " sweat or $\frac{3}{4}$ " male IPS
- Spread is NOT adjustable
- Check tub deck and tub measurements to assure the spout projects far enough into the tub
- Anti scald protection is the responsibility of the installer and according to applicable codes.
- Replacement cartridge - part # WWPTU11
- Optional 2" projection extension - part # WWPTU20

INSTALLATION GUIDELINES:

IMPORTANT:

- To ensure this product is installed properly, you must read and follow these guidelines.
- The owner/user of the tub filler must keep this information for future reference.
- Be sure your installation conforms to federal, state, and local codes. Anti scald protection is the responsibility of the installer and according to applicable codes.
- This tub filler should be on-site prior to rough in and allows the installer to visualize the installation and verify the center spread.
- An access panel must be installed for servicing and installation.
- Check tub deck and tub measurements to assure the spout projects far enough into the tub.

- Refer to the specification and assembly drawings attached. Faucet is sold partially assembled but shown fully disassembled for illustrative and service purposes only.
- Inspect this product to assure you have all parts required for proper installation.
- Use only a strap wrench or protected/smooth-jaw wrench on any finished surface.
- Install accessible hot and cold service stop valves to facilitate servicing.
- Do NOT use putty during this installation. Upper and lower washers are provided.

ROUGH IN:


- Note: There are 2 ways to connect the tub filler to the supplies; sweat/solder connection or IPS/threaded connection.
1. Run well supported $\frac{3}{4}$ " hot and cold supply lines for maximum water flow. The spread between supplies is $7\text{-}\frac{1}{4}$ " and is NOT adjustable. $1\text{-}\frac{1}{4}$ " drilling for the mounting holes is recommended.

TUB FILLER INSTALLATION:

2. Sweat/solder connections:
 - 2a. Unthread and remove the $\frac{3}{4}$ " Straight female x $\frac{3}{4}$ " IPS male adapter (1), both $\frac{3}{4}$ " washers (2,8), the mounting nut (3), and gasket (4) from the deck union (7).
 - 2b. To ensure a good connection, wire brush the union inlet to remove any excess finish.
 - 2c. Grasp the finished end of the union with a wet towel to prevent heat transfer when soldering that may damage the finish and then solder an appropriate length of $\frac{3}{4}$ " pipe to the union.
 - 2d. Thread the escutcheon (6) up the union until there are no exposed threads above the escutcheon and then insert the union into the deck, making sure the upper sealing gasket (5) is between the escutcheon and deck.
 - 2e. Adjust the supply line lengths as needed, reinstall the mounting gasket and then the nut and complete final solder connections.
 - 2f. Tighten the mounting nut up against the underside of the deck.
3. IPS/Threaded connections:
 - 3a. Unthread and remove the $\frac{3}{4}$ " Straight female x $\frac{3}{4}$ " IPS male adapter (1), both $\frac{3}{4}$ " washers (2,8), the mounting nut (3), and gasket (4) from the deck union (7).
 - 3b. Thread the escutcheon (6) up the union until there are no exposed threads above the escutcheon and then insert the union into the deck, making sure the upper sealing gasket (5) is between the escutcheon and deck.

- 3c. Reinstall the mounting gasket and then the nut onto the union.
 - 3d. Apply pipe thread compound to the union, insert a 3/4" rubber washer (2) into the adapter (1) and then thread the adapter onto the union.
 - 3e. Apply pipe thread compound onto the male end of the adapter and then thread it into a 3/4" female IPS x sweat adapter.
 - 3f. Adjust the supply line lengths as needed and complete final connections.
 - 3g. Tighten the mounting nut up against the underside of the deck.
 - 4. Install a 3/4" washer (8) into each inlet and then attach the tub filler to the deck unions by tightening the nuts (27) on the back side of the tub filler.
 - 5. Insert a 3/4" washer (24) into the base of the cradle (16) and then secure the cradle to the tub filler by tightening the nut (16a). The cradle can be positioned with the hose outlet pointing left or right.
 - 6. Thread one end of the hose (9) onto the vacuum breaker (18) and then thread the other end onto the hand shower (11-15), making sure a 1/2" washer (10,19) is included at both connection points. Note a combination check valve with flow restrictor is located inside the base of the hand shower (11).
 - 7. Rotate the diverter lever (44-47) to the left and then turn the hot and cold water on to flush the lines through the spout. Rotate the lever to the left and right to make sure water is diverting properly between the spout and hand shower.
 - 8. As always, check for leaks at all connections.
 - 9. Install the indices marked "hot" and "cold" onto the proper handle using the double sided adhesive pads.
 - 10. To service a valve stem (34), loosen the handle cover (35) and then remove the handle assembly (35-37).
- If further assistance is required, please contact Product Support at 1-800-927-2120 (8am-7pm EST).

These guidelines have been prepared for the professional contractor to aid in the installation of:
EASTON® EXPOSED TUB FILLER (EATU21,22-K,24-K,25-K,31,32-K,34-K,35-K)
EASTON® DECK UNIONS (EATU16)



⑳* = 3mm hex screw

㉔* = part # WWPTU11

12/03 These guidelines have been prepared for the professional contractor to aid in the installation of:
EASTON® EXPOSED TUB FILLER (EATU21,22-K,24-K,25-K,31,32-K,34-K,35-K)
EASTON® DECK UNIONS (EATU16)

All dimensions are based on original specifications and are subject to change and variation.
 Please consult your Design Associate for current specifications.

W A T E R W O R K S®

CARE AND CLEANING

The lustrous finish on your fitting or fixture should be treated with care. Improper handling or cleaning can damage the surface of any finish and void the warranty.

To clean the finish, wipe gently with a soft, damp cloth and then with a soft, dry towel. A mild soap solution can be used for daily cleaning. THE USE OF UNAUTHORIZED POLISHES, ABRASIVE CLEANERS, SOLVENTS, AMMONIA-BASED PRODUCTS, OR ACID BASE CLEANERS MAY DAMAGE THE FINISH AND WILL VOID THE WARRANTY.

Water contains lime and other minerals that are deposited after the water has evaporated. You can prevent deposits from forming by always wiping the fitting dry after use.

In addition to the aforementioned care instructions, the following points are specific to certain finishes or products only. Always read and follow the instructions when using any cleaning or polishing products.

NON-METAL TUBS

In addition to mild soap and water, a non-abrasive basin tub and tile cleaner is recommended for regular cleaning and disinfecting. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty.

WHIRLPOOL AND AIRTUB SYSTEMS

Jet Fresh whirlpool cleaning solution is recommended for maintaining waterways.

ANTIQUED COPPER AND BRASS

Select Waterworks fittings and basins are offered in finishes that have been artificially weathered, creating a patina that will develop and change with time. In addition to mild soap and water, a natural citrus-based product may be used for regular cleaning. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty. Please note that prolonged contact with certain items such as toothpaste, acidic fruits and vegetables, and wines will alter the surface finish. Also, the use of polishing agents will remove the patina and restore the metal to its original shine. Once removed, the patina will naturally redevelop with time.

ARCHITECTURAL BRONZE

In addition to mild soap and water, a natural citrus-based product may be used for regular cleaning. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty. Please note that prolonged contact with certain items such as toothpaste, acidic fruits and vegetables, and wines will alter the surface finish. Also, the use of polishing agents will remove the finish.

CHINA, CERAMIC AND PORCELAIN

Do not use abrasive cleaners, as this will dull the surface finish. A non-abrasive basin tub and tile cleaner is recommended for regular cleaning and disinfecting. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty.

CHROME

In addition to mild soap and water, a non-abrasive basin tub and tile cleaner is recommended for regular cleaning and disinfecting. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty. Cape Cod Polishing Cloths may be used for the occasional polishing. If you desire additional protection, the use of Faucet Brite will aid in protecting the surface finish from mineral deposits present in your water supply. This should be reapplied as necessary to continue protection.

MATTE NICKEL, LUMIN AND GOLD

In addition to mild soap and water, a non-abrasive basin tub and tile cleaner is recommended for regular cleaning and disinfecting. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty. Also, the use of polishing agents will remove the finish. If you desire additional protection, the use of Faucet Brite will aid in protecting the surface finish from mineral deposits present in your water supply. This should be reapplied as necessary to continue protection.

NICKEL

In addition to mild soap and water, a non-abrasive basin tub and tile cleaner is recommended for regular cleaning and disinfecting. The use of any other cleaners or disinfectants may alter the surface finish and void the warranty. Cape Cod Polishing Cloths may be used for the occasional polishing. The use of any other polishing agents will remove the finish and void the warranty. If you desire additional protection, the use of Faucet Brite will aid in protecting the surface finish from mineral deposits present in your water supply. This should be reapplied as necessary to continue protection.

SILVER

Fittings offered in a silver finish will tarnish with age. This finish may be restored to its original luster by using Faucet Brite or a non-abrasive silver polish. This should be reapplied as necessary to continue protection. Faucet Brite will also help to prolong the time between regular polishing.

UNLACQUERED BRASS AND COPPER

Items purchased in the unlacquered brass and copper finishes will change with time as they develop a natural patina. The original shine can be restored using Faucet Brite or an appropriate polishing compound. If you desire additional protection, the use of Faucet Brite will aid in protecting the surface finish from mineral deposits present in your water supply and prolong the time between regular polishing. This should be reapplied as necessary to continue protection.

WARRANTY

LIMITED LIFETIME MECHANICAL WARRANTY:

Waterworks warrants to the initial purchaser all plumbing and accessory products sold by Waterworks, which are installed in a residence to be used in a residential application, to be free from manufacturing defects in materials and workmanship for as long as the purchaser continues to own and maintain the residence where the products are initially installed.

FIVE-YEAR FINISH WARRANTY:

Waterworks warrants to the purchaser the finish of all plumbing and accessory products sold by Waterworks, which are installed in a residence to be used in a residential application, to be free from manufacturing defects in materials and workmanship for a period of five years from installation of the products. Waterworks must receive notice of any warranty claim within the five-year warranty period.

REPAIR OR REPLACEMENT:

If within the applicable warranty period the covered products shall be proved to the satisfaction of Waterworks to be defective, Waterworks will repair or replace such products, at its expense (provided that such repair or replacement shall not include installation costs). Waterworks' obligation shall be limited to such repair and replacement and shall be conditioned upon Waterworks' receiving notice of any alleged defect within the applicable warranty period. Purchaser shall be responsible for all shipping charges for returned products.

LIMITATIONS ON WARRANTY COVERAGE:

The warranties set forth above shall be extended only to the purchaser and do not apply to any purchaser where the products are used for commercial applications and usage. Furthermore, the warranties do not cover installation or any other labor charges and do not apply to:

- (i) products which have been repaired, altered or modified in any way by purchaser or any person other than Waterworks or not using original Waterworks spare parts, unless previously authorized in writing by Waterworks;
- (ii) products which have not been installed, used, maintained or stored in accordance with the instructions provided to purchaser by Waterworks;
- (iii) products which have been used for purposes other than or in a manner contrary to their intended and normal use;
- (iv) products which have been damaged as a result of misuse, negligence, freezing, accident or faulty installation or maintenance; and
- (v) products damaged by the effects of dirt, salt water air, hard water, limescale, or abrasive or aggressive cleaners. If the normal life span of any product is shorter than the applicable warranty period, the warranty shall apply only during the period of such shorter life span.

NOTICE OF WARRANTY CLAIMS:

For all warranty claims please call Waterworks Product Support at 800-927-2120, or write to Waterworks Product Support at 60 Backus Avenue, Danbury, Connecticut 06810.

The warranties provided herein are conveyed only to the purchaser of products sold by Waterworks after January 1, 2000, and installed in a residential application.

Except as specifically set forth above, Waterworks does not make any other warranty, express or implied, including without limitation, any implied warranty of merchantability or fitness for a particular purpose. In no event shall Waterworks be liable to any person or entity for any indirect, special, incidental or consequential damages or loss (including damages for loss of business, loss of profits, or the like), whether based on breach of contract, tort (including negligence), product liability or otherwise, even if it has been advised of the possibility of such damages.

Waterworks' liability on any claim of any kind, including negligence, shall in no case exceed the contract price paid by the purchaser for the product claimed to be defective or unsuitable.