

BRETFORD BASICS™

UL LISTED FLAT PANEL WIDE BODY CART

FPBBUL37 Series FOR FLAT PANEL MONITORS to 75 LBS

FPBBUL37 Flat Panel Carts have been certified to comply with UL standard 1667 for tall institutional carts.

For use with flat panel monitors not to exceed 75 lbs., 34.02 kg. Suggested use with 36" to 47" flat panel.



Now available with a new and improved 6-outlet power strip!

FEATURES

- Stability and load tested by Underwriter Laboratories for safe use with a flat panel monitor up to 75 lbs., 34.02 kg. in the United States and Canada. Any size monitor is appropriate as long as it does not exceed the maximum weight load, suggested for use with 36" to 47" flat panels
- Universal mounting bracket is adjustable to fit the unique mounting hole pattern on the back of your monitor up to 700 mm wide by 400 mm tall, so there is no guess work on what monitor you can use. And you don't need a new cart just because you changed monitors.
- Monitor can be set at a 0°, 7-1/2° or 15° forward angle to reduce glare and provide the best angle for your audience.
- Integrated cord management keeps things neat and in their place and reduces the risk of snagging a cord during transport.
- A top shelf handle makes it easier to push the cart from one location to another by providing additional room to walk behind the cart.
- Wide body, pyramid design and sturdy steel construction lowers the center of gravity and provides superior stability.
- Top shelf includes a 22" monitor mounting pole and measure 36-1/4"w x 23-3/4"d. Top shelf is 44" off the floor.
- Middle shelf measures 36-1/4"w x 23-3/4"d (10-1/2" between top and middle shelves) and is ideal for use with a DVD and speakers.
- Bottom shelf measures 36-1/4"w x 28-3/4"d (22-1/2" between shelves) and works well with heavier equipment or as storage.
- Optional UL & C-UL listed 6-outlet electrical unit with surge and overload protection, a 20 foot power cord and built-in cord winder included with the FPBBUL37-E5BK and FPBBUL37-M5BK.
- 5" industrial grade plate casters - two fixed and two swivel and lock.
- FPBBUL series carts feature a steel content with 25% to 35% post-consumer recycled steel and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. FPBBUL series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.

A HIGHER FORM OF FUNCTION



BRETFORD

DIMENSIONS

Overall: 36-1/4"w x 28-3/4"d x 66"h (monitor not included in height)
Top and Middle Shelves: 36-1/4"w x 23-3/4"d
Bottom Shelf: 36-1/4"w x 28-3/4"d
Middle to Top Shelf: 10-1/2"
Bottom to Middle Shelf: 22-1/2"
Aluminum Mounting Pole: 22"l
Mounting Arm Plate: 31"w
Mount Arm Adjustability: 100-700mm (3.94"-27.56") wide
100-400mm (3.94"-15.75") high
Forward Tilt Adjustment: 0°, 7-1/2°, 15°

COLOR & FINISH

Black (-BK) powder paint

STANDARD EQUIPMENT

(2) 36-1/4"w x 23-3/4"d Shelves
(1) 36-1/4"w x 28-3/4"d Bottom Shelf
(1) Top Shelf Handle
(1) 22"l Aluminum Mounting Pole
(2) Monitor Mounting Arms
(1) Monitor Arm Mounting Plate
(1) Angle Adjustable Mounting Box
(1) Aluminum Mounting Nugget
(4) 5" Plate Casters, (2) Fixed and (2) Swivel and Locking
(1) Red Plastic Bag with Hardware for Assembly
(1) 6-Outlet Electrical Assembly (*FPBBUL37-E5BK & M5BK only*)

WEIGHT, FRT CLASS, CARTON DIMS & UPC CODE

FPBBUL37-P5BK: 120 lbs., Freight class 70
0 96633 30784 5

FPBBUL37-E5BK: 123 lbs., Freight class 70
0 96633 30785 2

FPBBUL37-M5BK: 123 lbs., Freight class 70
0 96633 30786 9

Carton Pack: 41"w x 37"d x 10"h, 8.78 cubes

All models ship ready-to-assemble in one (1) carton pack and are available to ship LTL truck.

ACCESSORIES

FPTVULM4 - Monitor Metric M4 Security Screws - 0 96633 31751 6
FPTVULM5 - Monitor Metric M4 Security Screws - 0 96633 31752 3
FPTVULM6 - Monitor Metric M4 Security Screws - 0 96633 31753 0
FPTVULKEY - Metric Security Screw Key - 0 96633 31754 7



MADE IN THE USA

The FPBBUL series flat panel carts are made at Bretford's Chicago area manufacturing facility using union labor.



ENVIRONMENTAL SPECIFICATIONS

The FPBBUL series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. FPBBUL series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

SAFETY RATING SPECIFICATIONS

FPBBUL37 Flat Panel Wide Body Carts have been tested by Underwriter Laboratories and certified to comply with UL standard 1667 for tall institutional carts and is designated for use with flat panel monitors up to 75 lbs., 34.02 kg. Certified for the United States and Canadian markets.

ELECTRICAL UNIT SPECIFICATIONS

Optional electrical assembly includes six (6) grounded outlets, 20 ft. 3-wire power cord, cord winder, and surge/overload protection. Units attach to pre-drilled holes in the top or middle shelf and are UL listed when attached to the FPBBUL37 cart. Electrical units are included as standard on models FPBBUL37-E5BK and model FPBBUL37-M5BK.

MONITOR MOUNTING SPECIFICATIONS

The monitor assembly has two arms that secure to the mounting holes in the back of the monitor and hang on a horizontal plate that secures to the aluminum pole. Arms are adjustable to fit the mounting hole pattern on the back of the monitor from 100 mm to 700 mm wide and 100 mm to 400 mm high. A transition plate has forward tilt adjustment settings of 0°, 7-1/2° or 15° and is designed to prevent slipping of the monitor's angle when in transit.

CART ASSEMBLY SPECIFICATIONS

FPBBUL37 carts include two (2) 18-gauge steel 36-1/4"w x 23-3/4"d shelves and one (1) 18-gauge 36-1/4"w x 28-3/4"d bottom shelf. Shelves are press formed with a 1/8" lip bordering the top surface on all four (4) sides to help prevent materials from sliding off. Legs fit flush to the shelves and interlock with mounting brackets for added strength. Each corner has 13-gauge steel mounting brackets with 1/4" square head bolts and hex nuts that tighten to hold leg securely to the shelf. The two (2) 36-1/4"w x 23-3/4"d shelves have two (2) 3/16" diameter holes centered on both the right and the left side to accept an optional electrical assembly. Top shelf has reinforced plating on the underside and mounting holes for an aluminum pole and supports a handle for pushing the cart. Aluminum mounting pole is 22"l and allows a flat panel monitor to be mounted to the front side, the back side includes mounting stops. The front and rear of the pole include a cord management channel. Legs are 18-gauge 1" square tubular steel. Each leg is 39-1/2" in length and tapered so the top section fastens to two 36-1/4"w x 23-3/4"d shelves and the bottom fastens to a 36-1/4"w x 28-3/4"d base shelf. The cart stands 66"h (not including the monitor), top shelf is 44"h. Plate casters are mar resistant hard black rubber and measure 5" in diameter. Two (2) casters are fixed and two (2) swivel and lock. Carts are finished in a durable and environmentally friendly Black Pumice powder paint. All carts ships knocked down (KD) in one carton pack and are available to ship via LTL truck.

11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM