

BRETFORD BASICS™

UL LISTED FLAT PANEL WIDE BODY CABINET CART

FPBBULC32 Series

FOR FLAT PANEL MONITORS TO 65 LBS

FPBBULC32 Flat Panel Carts have been certified to comply with UL standard 1667 for tall institutional carts.

For use with flat panel monitors not to exceed 65 lbs., 29.5 kg. Suggested use with 30" to 42" flat panel.



Now available with a new and improved 6-outlet power strip!



FEATURES

- Stability and load tested by Underwriter Laboratories for safe use with a flat panel monitor up to 65 lbs., 29.5 kg. in the United States and Canada. Any size monitor is appropriate as long as it does not exceed the maximum weight load, suggested for use with 30" to 42" flat panels.
- Universal mounting bracket is adjustable to fit the unique mounting hole pattern on the back of your monitor up to 700 mm wide by 400 mm tall, so there is no guess work on what monitor you can use. And you don't need a new cart just because you changed monitors.
- Monitor can be set at a 0°, 7-1/2° or 15° forward angle to reduce glare and provide the best angle for your audience.
- Integrated cord management keeps things neat and in their place and reduces the risk of snagging a cord during transport.
- A top shelf handle makes it easier to push the cart from one location to another by providing additional room to walk behind the cart.
- Locking lower cabinet provides secure storage for expensive electronics, CDs, speakers, and other supplies, and includes a grommet hole to manage cords and allow equipment to be used inside the cabinet. Lower cabinet interior provides a 30"w x 26"d x 16-3/4"h storage space.
- Lower cabinet, wide body, pyramid design and sturdy steel construction lowers the center of gravity and provides superior stability.
- Top shelf includes a 22" monitor mounting pole and measure 32"w x 22"d. Top shelf is 48" off the floor. Middle and bottom shelves measures 32"w x 27-1/2"d. (20" between top and middle shelves.)
- Optional UL & C-UL listed 6-outlet electrical unit with surge and overload protection, a 20 foot power cord and built-in cord winder included with the FPBBULC32-E4BK and FPBBULC32-M4BK.
- 4" industrial grade casters - two fixed and two swivel.
- FPBBUL series carts feature a steel content with 25% to 35% post-consumer recycled steel and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. FPBBUL series carts also comply with the GREENGUARD Environmental Institute's GREENGUARD Children & Schools Indoor Air Quality standards contributing to points toward Leadership in Energy and Environmental Design (LEED) Certification.
- Made in the USA.

A HIGHER FORM OF FUNCTION



BRETFORD

DIMENSIONS

Overall: 32"w x 27-1/2"d x 70"h (monitor not included in height)
Top Shelf: 32"w x 22"d
Middle & Bottom Shelf: 32"w x 27-1/2"d
Cabinet Interior: 30"w x 26"d x 16-3/4"h
Middle to Top Shelf: 20"
Aluminum Mounting Pole: 22"
Mounting Arm Plate: 31"w
Mount Arm Adjustability: 100-700mm (3.94"-27.56") wide
100-400mm (3.94"-15.75") high
Forward Tilt Adjustment: 0°, 7-1/2°, 15°

COLOR & FINISH

Black (-BK) powder paint

STANDARD EQUIPMENT

(1) 32"w x 22"d Shelves
(1) 30"w x 26"d x 16-3/4"h Cabinet
(1) Top Shelf Handle
(1) 22"l Aluminum Mounting Pole
(2) Monitor Mounting Arms
(1) Monitor Arm Mounting Plate
(1) Angle Adjustable Mounting Box
(1) Aluminum Mounting Nugget
(4) 4" Casters, (2) Fixed and (2) Swivel
(1) Red Plastic Bag with Hardware for Assembly
(1) 6-Outlet Electrical Assembly (FPBBULC32-E4BK & M4BK only)

WEIGHT, FRT CLASS, CARTON DIMS & UPC CODE

FPBBULC32-P4BK: 121 lbs., Freight class 70, LTL truck
0 96633 30781 4
FPBBULC32-E4BK: 123 lbs., Freight class 70, LTL truck
0 96633 30782 1
FPBBULC32-M4BK: 123 lbs., Freight class 70, LTL truck
0 96633 30783 8
Carton Pack: 51"w x 33"d x 9"h, 5.67 cubes
All models ship ready-to-assemble in one (1) carton pack.

ACCESSORIES

FPTVULM4 - Monitor Metric M4 Security Screws - 0 96633 31751 6
FPTVULM5 - Monitor Metric M4 Security Screws - 0 96633 31752 3
FPTVULM6 - Monitor Metric M4 Security Screws - 0 96633 31753 0
FPTVULKEY - Metric Security Screw Key - 0 96633 31754 7

MADE IN THE USA

The FPBBUL series flat panel carts are made at Bretford's Chicago area manufacturing facility using union labor.

ENVIRONMENTAL SPECIFICATIONS

The FPBBUL series carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and an extruded aluminum which has an average of 90% post-consumer recycled content. All steel and aluminum components are recyclable at the end of the product life cycle. FPBBUL series carts are certified to GREENGUARD Children & Schools Indoor Air Quality standards.

SAFETY RATING SPECIFICATIONS

FPBBULC32 Flat Panel Wide Body Carts have been tested by Underwriter Laboratories and certified to comply with UL standard 1667 for tall institutional carts and is designated for use with flat panel monitors up to 65 lbs., 29.5 kg. Certified for the United States and Canadian markets.

ELECTRICAL UNIT SPECIFICATIONS

Optional electrical assembly includes six (6) grounded outlets, 20 ft. 3-wire power cord, cord winder, and surge/overload protection. Units attach to pre-drilled holes in the top or middle shelf and are UL listed when attached to the FPBBULC32 cart. Electrical units are included as standard on models FPBBULC32-E4BK and model FPBBULC32-M4BK.

MONITOR MOUNTING SPECIFICATIONS

The monitor assembly has two arms that secure to the mounting holes in the back of the monitor and hang on a horizontal plate that secures to the aluminum pole. Arms are adjustable to fit the mounting hole pattern on the back of the monitor from 100 mm to 700 mm wide and 100 mm to 400 mm high. A transition plate has forward tilt adjustment settings of 0°, 7-1/2° or 15° and is designed to prevent slipping of the monitor's angle when in transit.

CART ASSEMBLY SPECIFICATIONS

FPBBULC32 carts includes one (1) 18-gauge steel 32"w x 22"d shelf with underside reinforcement and two (2) 18-gauge 32"w x 27-1/2"d shelves for the middle and bottom section. Shelves are press formed with a 1/8" lip bordering the top surface on all four (4) sides to help prevent materials from sliding off. Includes a lower cabinet section with two (2) side panels, one (1) rear panel, and two (2) front door panels. Side panels are constructed from 18-gauge steel and doors are constructed of 20-gauge steel. Doors consist of a left and a right panel, mount with full length piano hinges allowing 180° opening, and have recessed handles. The right door panel includes a 16-gauge steel locking bar with installed lock and two (2) keys. Legs fit flush to the shelves and interlock with mounting brackets for added strength. Each corner has 13-gauge steel mounting brackets with 1/4" square head bolts and hex nuts that tighten to hold leg securely to the shelf. The top shelf has mounting holes for an aluminum pole and supports a handle for pushing the cart. Aluminum mounting pole is 22"l and allows a flat panel monitor to be mounted to the front side, the back side includes mounting stops. The front and rear of the pole include a cord management channel. Legs are 18-gauge 1" square tubular steel. Each leg is 44" in length and tapered so the top section fastens to the 32"w x 22"d top shelf and the middle and bottom fastens to the 32"w x 27-1/2"d shelves. The cart stands 70"h (not including the monitor), top shelf is 48"h. Casters are mar resistant hard black rubber and measure 4" in diameter. Two (2) casters are fixed and two (2) swivel. Carts are finished in a durable and environmentally friendly Black Pumice powder paint. All carts ships knocked down (KD) in one carton pack and are available to ship via LTL truck.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM