

# \*\*AMERICANSEATING

Upholstery Fabrics by Momentum
Grade 2

# Upholstery Fabrics GRADE 2



Perk

GLT Cedar E

Russo

GLF Imperial  $\it E$ 



Jargon FKF Peacock *E* 



Insight GKQ Midnight *E* 



Expo GKH Sky *E* 



Insight GKS Periwinkle *E* 



Context FKP Lake *E* 



Pivot GKA Lagoon *E* 



Perk GLU Cabana *E* 



Perk GL2 Patriot *E* 



Jargon FKE Nautica *E* 



Context FKN Jam *E* 



Pivot GKD Orchid *E* 



Insight GKY Concord *E* 



Expo GKM Viola *E* 



Context FKV Skylar *E* 



Perk GLX Regal *E* 



Insight GKX Eggplant *E* 



Perk GLV Walnut *E* 



Perk GL3 Pewter *E* 



Russo GLH Shadow *E* 



Insight GK3 Ebony *E* 



Perk GL0 Flint *E* 



Jargon FKA Spiffy *E* 



Expo GKN Fog *E* 



Perk GL4 Ebony *E* 



Insight GKT Fossil *E* 



Expo GKP Tuxedo *E* 



Context FKL Cement *E* 



Insight GK1 Summit *E* 



Pivot GKG Tower *E* 

## Grade 2

### Essentials Program

All fabrics in this collection are available for **Essentials**, American Seating's quick-ship program, denoted with an E.

### Customer's Own Material (COM)

Customers may specify COM fabric line for use on American Seating products. Samples of the COM line must be submitted to American Seating prior to order placement. Your American Seating sales representative or dealer can provide exact procedures for approval of a COM fabric.

American Seating employs specific quality control procedures in the acceptance of all fabric lines. Industry-wide color tolerances allow for slight dye lot variations among fabric runs.

RUSSO	
Grade Level 2	
45% Rayon, 55% Polyester	
Weight	0.62 lb per linear yard
Width	58"
Directional	Yes
Racking	Vas - Acrylic

Flammability CA Bulletin 117 Sec. E UFAC Class 1

NFPA 260 Abrasion

Resistance 33,000 double rubs AATCC16A Class 5.0; 40 hours **Light Fastness** Surface Finish Soil and stain resistance

Cleaning Code

**EXPO** Grade Level 2

65% Post Industrial Recycled Polyester 35% Post Consumer Recycled Polyester Weight 0.34 lb. per linear yard

54" Width Directional No

Backing Yes - Acrylic Flammability CA Bulletin 117 Sec. E

UFAC Class 1 NFPA 260

Abrasion

Resistance 102,000 double rubs Light Fastness AATCC16A Class 5.0; 40 hours Surface Finish Soil and stain resistance

Cleaning Code

**PIVOT** Grade Level 2 100% Polyester

0.81 lb. per linear yard Weight

Width 54' Directional No

Backing Yes - Acrylic Flammability CA Bulletin 117 Sec. E

UFAC Class 1 NFPA 260

Abrasion

Resistance 39,000 double rubs

Light Fastness AATCC16A Class 5.0; 40 hours Surface Finish Soil and stain resistance

Cleaning Code WS CONTEXT Grade Level 2

65% Post Industrial Recycled Polyester 35% Post Consumer Recycled Polyester

0.64 lb. per linear yard Weight Width 54" Directional No

Backing Yes - Acrylic

Flammability CA Bulletin 117 Sec. E

UFAC Class 1 NPFA 260

Abrasion 57,000 double rubs Resistance AATCC16A Class 4.0; Light Fastness

40 hours

Surface Finish Soil and stain resistance Recycled fiber content Environment

Cleaning Code

**PERK** 

Grade Level 2 100% Polyester

0.98 lb. per linear yard Weight

Width 54" Directional No Backing Yes - Latex

Flammability CA Bulletin 117 Sec. E

NFPA 260

Abrasion 102,000 double rubs Resistance Light Fastness AATCC16A Class 5.0;

40 hours Soil and stain resistance

Surface Finish

Cleaning Code

INSIGHT Grade Level 2 100% Polyester

Weight 0.75 lb. per linear yard

Width 54' Directional No Backing

Yes - Acrylic Flammability CA Bulletin 117 Sec. E

UFAC Class 1 NFPA 260

Abrasion

192,000 double rubs Resistance AATCC16A Class 5.0; **Light Fastness** 

40 hours

Surface Finish Proprietary stain resistance

Cleaning Code

**JARGON** Grade Level 2 100% polyester

Weight 0.80 lb. per linear yard Width 54'

Directional

Backing Yes - Acrylic

CA Bulletin 117 Sec. E Flammability

UFAC Class 1 NFPA 260

Abrasion Resistance 90,000 double rubs AATCC16A Class 4.0; **Light Fastness** 

40 hours

Surface Finish Soil and stain resistance Environment Recycled fiber content

Cleaning Code

S - Only pure, water-free solvents may be used. CAUTION: Use of water-based or detergentbased solvents may cause shrinking and/or permanent water stains.

WS - Clean with water-based cleaning agent, foam or pure, water-free solvents. Vacuuming or light brushing is recommended to prevent dust and soil build-up.

The printed colors on these pages are representative of our fabric offering. Actual material samples should be requested for final fabric selection.

Memo samples for projects available online at memosamples.com or call 800.366.6839.





401 American Seating Center Grand Rapids, MI 49504-4499 Phone 616-732-6600 800-748-0268 FAX 616-732-6401 americanseating.com



