

Commander® Shower Cabinets



FIAT®

Models S-115 and S-125

These shower cabinets are the ultimate in planned custom comfort for disabled and elderly people.

COMFORT AND CONVENIENCE

The specially-designed phenolic seat combines aesthetics and durability and is easily folded out of the way when not in use. The stainless steel grab bars are designed for maximum convenience as is the hand held shower and slide guide.

Critical areas are additionally reinforced to safely accept the seat and grab bars.

WHEELCHAIR ACCESSIBLE

A half-inch receptor threshold entry height accommodates ease of wheelchair accessibility.

LEAK-PROOF STRENGTH AND DURABILITY

Both side and back walls of the cabinets are "Wonder Wall" designed sandwich panels with an inside core of water impervious insulation permanently laminated to wall panels with waterproof adhesive. Inner and outer wall surfaces are made of galvanized-bonderized steel finished in white (or selected colors) baked-on enamel joined with anodized aluminum extruded molding. The top frame is made of one-piece welded construction with double barrier field-assembled joints to ensure leakproof connections. The 6" (152) high terrazzo shower floor is made of black and white marble chips cast in portland cement, ground and polished to assure comfort and "bring out" the beauty of the marble.

CABINET SIZES

- Model S-115 -- 39" x 39" x 82" (991 x 991 x 2083) with 32" (813) entrance. Shipping Weight : 600 lb./273 kg
- Model S-125 -- 39" x 48" x 82" (991 x 1219 x 2083) with 32" (813) entrance. Shipping Weight: 750 lb./341 kg
- Specify LH or RH when ordering



SPECIFICATIONS

- Integrally cast stainless steel drain body provides for a caulked lead connection or quick drain connector not less than 1" (25) deep to a 2" (51) pipe
- Receptor has integral stainless steel entry cap, Integrally cast, galvanized-bonderized steel tiling flange extends 1½" (38) above the shoulder which is 4" (102) high and 3" (76) wide
- Model 190AA Pressure balanced single lever mixing valve with maximum limit temperature stop, service stops and integral volume control
- Package consisting of a wall hung shower head and 69" (1753) stainless steel hose with in-line vacuum breaker, supply elbow, flange and 24" (610) slide guide with hanger hook
- One wrap around horizontal and one vertical 1¼" (32) O.D. stainless steel grab
- One folding handicapped wheelchair shower transfer seat of phenolic with seat frame and support constructed of stainless steel tubing
- 10 ounce shower curtain with hooks
- Stainless steel 1" (25) diameter curtain rod with brass chromium plated brackets
- Brass chromium-plated soap dish

ALTERNATE CABINET FINISHES

Inner surfaces of stainless steel type 304-4B finish. Outer surfaces of galvanized-bonderized steel finished in white (or selected colors) synthetic baked-on enamel or type 304-4B finish stainless steel.

OPTIONS

- Model 192AA thermostatically controlled single lever mixing valve with service stops
- Top cover in same finish as interior walls
- Dome light, Model 1001/1021 for use with top cover

NOTE

Establish ¼" clearance between building walls and shower floor. All units must be leveled and set in a bed of mortar. It is recommended that a floor drain be installed at the entrance to the shower.

Fiat Products Ltd. also carries a complete line of acrylic wheelchair accessible showers. Please contact Customer Service for more information.



FIAT PRODUCTS®
A CRANE PLUMBING COMPANY

255 Hutchings St. • Winnipeg, MB • R2X 2R4 • Ph. 800-665-7531 • 204-633-6122 • Fx. 204-632-4854
e-mail: info@fiat.ca • website: www.fiat.ca

A subsidiary of CR/PL, L.L.C. Company – Evanston, IL