



**General:**

Precast terrazzo one piece products are made of black and white marble chips cast in grey portland cement to produce a compressive strength of not less than 3000 P.S.I., seven days after casting. The terrazzo surface is ground and polished with all air holes and/or pits grouted and the excess removed. Mop service basins are available in custom sizes.

TSBC 6010 series neo-corner model 12" (305) high available with stainless steel caps on all curbs. Shoulders shall not be less than 2" (51) wide with 1/2" (13) pitch toward inside.

The drain body in mop basins are made of stainless steel cast integrally and provide for a caulked lead connection not less than 1" (25) deep to a 3" (76) pipe.

**Installation:**

Establish 1/4" (6) clearance between mop service basin and building wall. It is required that the entire area between the mop service basin and the building floor has a 1/2" (13) layer of mortar in order that the mop service basin is level.

Optional stainless steel tiling flanges available.

WITH STAINLESS STEEL CAPS ON ALL CURBS								
MODEL	SIZE	APPROX. SHIP WT.	A	B	C	D	E	F
TSBC 6010	24 x 24 x 12	255 lbs/116 kg	24(610)	24(610)	12(305)	12(305)	11(279)	18 1/4 (464)
TSBC 6011	32 x 32 x 12	420 lbs/191 kg	32(813)	32(813)	12(305)	12(305)	14(356)	25 3/8 (645)
TSBC 6012	36 x 36 x 12	485 lbs/220 kg	36(914)	36(914)	12(305)	12(305)	18(457)	25 3/8 (645)

**NOTE:** In the 24" x 24" x 12" model the drain location as shown in drawing would actually be located closer to the front of dimension "F". Drawing not to scale.

