

Trillium

NEW TLED personal task light

TLED personal desk light includes:


- 6.5 watt fixture @700mA
- Warm yet broad pool of illumination at 3500K or 3000K
- 7' black cord with disconnect to power supply
- 120 VAC, 50/60 HZ input with 8' black cord with molded straight plug
- Black rocker switch, 2 position
- Parabolic lens
- Double-articulating arm
- Durable die cast aluminum head
- Multiple mounting choices - must specify
- Finish - black
- UL and CUL listing



Base Number	Description
TLED	6.5 watt double-articulating arm

Arm options:

Double arm (D) two straight arms, both arms move up and down. This option is ideal for large work spaces or offices where the mounting point is far from the task to be illuminated.



Specifying notes:

- The power supply features an 8' cord with quick disconnect allowing the user to install the light easily into new or existing installations.
- Total length, including the AC connection cord and fixture cord, is approximately 15'.
- The arm and head can be transferred from one base to another to accommodate reconfigured offices. Select the base / mounting application from the list on the next page.
- Panel mount design varies slightly with office furniture system panel.
- Cord managers available as an option for panel mount. See task light pages for cord manger information and pricing.
- The freestanding base has a footprint of 9" in diameter.
- Total weight of freestanding base is 9.3 pounds.

Trillium

NEW TLED personal task light

TLED base model prices

Base number less mounting	List Price
TLED	\$ 388.00

TLED option prices

Option	Description	Code	List Price
Mounting:	Freestanding	FS	\$117.00
	Clamp mount-min clearance	CMM	47.00
	Clamp mount-waterfall edge	CMW	57.00
	Panel mount	PM	42.00
	Surface mount	SM	36.00

Mounting options:

Freestanding (FS) weighted base is supplied as the standard unless otherwise specified.

Clamp mount minimum clearance (CMM) allows the TLED to be mounted to most freestanding or hanging work surfaces. Adjusts to fit surfaces up to 2.25" thick. Two-piece design simplifies installation in an existing workstation.

Clamp mount waterfall edge (CMW) allows the TLED to be mounted to most freestanding or hanging work surfaces. Fit surfaces 1 1/8" to 1 1/2" thick.

Panel mount (PM) allows the TLED to be mounted to various office furniture system panels. System must be specified. See mounting cross reference page 58.


Surface mount (SM) allows the TLED to permanently attach to a work surface.




freestanding base




clamp mount -
minimum clearance



clamp mount -
waterfall edge



panel mount



surface mount

How to specify the TLED personal task light

Example TLED CMM

1. base model
2. mounting option

1. Specify TLED.
2. Select mounting option.

When PM is selected, select code for manufacturer and system name of unit that the light will be mounting in.

If manufacturer and system name code is not listed, identify them on your purchase order and a Light Corporation customer service rep will contact you on availability.

Call Light Corporation customer service to place an order, 1-800-544-4899.
Prices are subject to change.