



SIMPLEX®

CEILINGS

255 Montpelier, St. Laurent
(Montreal) QC, Canada H4N 2G3
Tel: (800) 638-5726 Fax (514) 744-2716
www.simplexceilings.com

Specifications

Exterior Generation 2000 Series

- Panels:** Provide Simplex Ceilings Generation 2000 Planks system manufactured from 0.040" (1,016 mm) thick aluminum or thicker based on application. Plank dimensions will be as shown on drawings. Planks to be [un-perforated, perforated using pattern #___ with a {standard, ___ in. un-perforated border}].
- Finish:** Select from standards. Custom colors available upon request.
- Suspension:** Suspension shall be heavy-duty extruded aluminum Z-bar, to be attached to (1 ½") (2") "black iron" channel with adjustable Locking Suspension Brackets. Provide seismic or security clips for exterior applications.
- Perimeter:** Provide G-2000 Mould with hold down clips as required in finish to match panels.
- Acoustical:** For perforated panels, provide 1 ½" (38mm) thick x ¾ lb./cu ft (12 kg/cu m) density glass wool fiber completely sealed in a black incombustible (Class A) bag. Alternatively, provide non-woven acoustical liner laminated to back of perforated panel.
- Accessibility:** System is upwards demountable, providing progressive accessibility from specific access points.
- Standard Sizes:** 24" x 24", 24" x 48", 24" x 60", 24" x 96" and 24" x 120" (Other custom sizes available upon request.)
- Metric Sizes (mm):** 610 x 610, 610 x 1219, 610 x 1524, 610 x 2438 and 610 x 3048

