

LITHOCRETE CONDITIONER™
(Concrete Additive)

Product Description: Lithocrete Conditioner™ is a concrete additive that assists cement in its encasement of Lithocrete® surface-seeded aggregates.

Application Procedures: Before concrete is discharged from mixing barrel add (1) 5 gallon pail of Lithocrete Conditioner™ per full truckload (1/2 gallon per yard of concrete) minimum up to (2) 5 gallon pails of Lithocrete Conditioner™ per full truckload (1 gallon per yard of concrete) maximum. It is important to keep dosage rates consistent per jobsite. Rotate mixing barrel a minimum of 60 revolutions prior to discharge. Discharge concrete and check slump at point of discharge (i.e., end of pump hose).

The International Agency for Research on Cancer (IARC) has categorized Lithocrete Conditioner™ as a Class 2A carcinogen. A Class 2A carcinogen is one in which there is limited evidence for carcinogenicity in humans and sufficient evidence for carcinogenicity in experimental animals. Repeated or prolonged contact with skin or eyes may cause irritation. Wash hands immediately with soap and water; irrigate eyes immediately with copious amounts of water for 15 minutes. Consult physician, if necessary.

Limitations: The use of this material being subject to conditions beyond the Sellers control. Seller makes no warranty of any kind, expressed or implies, as to this material or its use.

WARNING: Use NIOSH/MSHA approved respirator, impervious gloves and safety goggles while handling product. Long-term exposure to respirable silica may produce pneumoconiosis in susceptible persons. May aggravate pre-existing respiratory conditions.