

PAVING SCHEDULE:

TYPE	DESCRIPTION	PATTERN	MODULE	THICKNESS	BASE	INTEGRAL COLOR	SAND (WCS)	COARSE AGGREGATE	CEMENT	Lithocrete® Aggregate	FINISH	JOINT WIDTH	REBAR	REMARKS
A	Lithocrete® Concrete Paving	Square	30" x 30"	4"	2" washed concrete sand	L.M. Scofield C-13 Tawny Pink	Reliance	Reliance 3/8" Pea Gravel	Riverside Type II or equal	Rosso Nero	Lithocrete™	1/8"	#3 at 18'o.c.e.w.	Lithocrete® is a patented paving process – match Shaw & Sons sample #00-XX.

PAVING SCHEDULE NOTES:

1. Verify layout of concrete paving indicated on Drawings and indicated on this paving schedule prior to starting Work. Contact Owner's Authorized Representative once paving forms have been laid out for review and approval.
2. Lithocrete® architectural concrete paving is installed under U.S. patents #4,748,788 and 6,016,635. Contact Lithocrete® at (949) 642-3473 or www.lithocrete.com for a list of licensed Lithocrete® installers in the project's area.
3. Refer to Specification #02521 – Lithocrete® Architectural Concrete Paving for additional paving information.
4. Construct paving indicated on this schedule per approved mock-ups.
5. Do not allow sawcut jointing to deviate more than (+/-) 1/16-inch overall in a 10-foot run. Of primary importance is that sawcutting is to be cut straight.
6. Construct paving mock-ups on-site for paving types described in this paving schedule for Owner's Authorized Representative review and approval. Approved samples are to remain on-site in an accessible location throughout duration of project. Approved samples will be basis for future paving work.