

AI 200 702 Stainless steel Air extraction /recirculation Width 40" (100 cm)

Installation accessories for exhaust air mode
AD 010 016
Stainless steel duct cover,
7' 3" - 7' 11" (2.23 - 2.41 m)
AD 010 026
Stainless steel duct cover,
7' 11" - 9' (2.41 - 2.73 m)
AD 010 036
Stainless steel duct cover,
9' - 9' 10" (2.72 - 2.99 m)

Installation accessories for recirculation air mode
AD 010 126
Stainless steel, duct cover,
7' 11" - 9' (2.41 - 2.73 m)
AD 010 136
Stainless steel, duct cover,
9' - 9' 10" (2.72 - 2.99 m)
KF 001 010
Activated charcoal filter

Island hood

AI 200

- Classic Gaggenau design.
- Air extration or recirculation system.
- Balance at a high level. High air output with minimal sound.
- Adjustable 80 watt soft halogen light: From bright to subdued lighting.

Output

Unobstructed air flow: 465 CFM with ø 6".

Sound pressure level: 61 dB.

Features

Three electronically controlled speeds and intensive mode, interval ventilation, delayed shut-off function, grease filter saturation display indicated by flashing lights.

Stainless steel grease filter, dishwasher-safe.

Soft-Light.

Planning notes

Duct cover required for installation.

Recirculating air operation:

A strong drop in output and clearly increased noise can be expected in the recirculating air mode in the case of hoods with a very high air output.

Minimum clearance from gas and electric appliances: 30".
The dimensions of the air ducts refer to a distance of 63" from the floor to the bottom edge of the hood. Convert for other installation heights: countertop height + minimum clearance + hood with

Weight: 53 lbs. Connecting cable: 47"

Rating

duct cover.

Total rating: 295 W Total Amps: 2.5 120V / 60Hz

Exhaust air:

AD 010-016 = 25 3 /16" - 32 5 /16" (640 - 820) AD 010-026 = 32 5 /16" - 44 7 /8" (820 - 1140) AD 010-036 = 44 7 /8" - 55 1 /8" (1140 - 1400)

Recirculating air:

AD 010-126 = 32 $^{5}/_{16}$ " - 44 $^{7}/_{8}$ " (820 - 1140) AD 010-136 = 44 $^{7}/_{8}$ " - 55 $^{1}/_{8}$ " (1140 - 1400)

