



StepByStep-I\_TY\_EN - 27.11.2009 - www.vs-furniture.com

## **PRODUCT INFORMATION**

## StepByStep-I Skid table, adjustable in height.

Frame of powder-coated steel tube with asymmetrically-positioned legs (cantilever) on steel skids with kicking protection. All steel tubes in round profile.

Frame size as per DIN ISO 5970 and CEN.

Frame features. Height adjustment in steps with hexagon key or hand-wheel.

Table top made from melamine-resin-coated LIGNOpal chipboard with a seamlessly cast-on safety edge made from (PU) polyurethane. Optionally with an extremely robust LIGNOdur safety top with softly rounded edges.

Features of top. Fixed horizontal working surface.

Accessories and options. Glides for hard and soft floors and briefcase (satchel) hooks. Plywood or grid bookshelf or chair suspension. For the models with LIGNOdur tops optionally with chair suspension elements for BasicGlide, LuPoGlide, PantoSwing (from size 4) and PantoMove.

**Important notice.** The table height can vary slightly depending on the type of top and the glides. PU edges are extremely robust, but can show signs of discoloration over time.

Following materials are available: Frame = M1,2; Top LIGNOdur= L1; Top LIGNOpal-PU = L1.

Other models illustrated on this page: PantoSwing-VF, Compass-VF.

		ISO/CEN  2 = 53 • 3 = 59 • 4 = 64 • 5 = 71 • 6 = 76 • 7 = 82	R			
StepByStep I	LIGNOdur-KU	d = 50	2904	2905		
	LIGNOpal-PU	d = 65			2993	2994
		W	70	130	75	130
		h	2·3·4·5·6·7			