











d1083

## d1080, d1082, d1083





Item Number	d1080	Flush mounted step lights w/full opal lens ADA
	d1082	Flush mounted step lights w/five slot grill <b>ADA</b>
	d1083	Flush mounted step lights w/three horizontal louvers ADA

Construction

Die-cast aluminum housing. Plastic opal lens (glass lens for incandescent version). Recess wall mounted and secured in position with two adjustable mounting brackets. Baked white enamel housing has two waterproof hubs for through wiring. UL listed for dry, damp and wet locations.

Lamping / Wattage	1N25	Incandescent, one 25 W, medium base, T type
Fixtures supplied less lamps.	1N40	Incandescent, one 40 W, medium base, T type
Lamps may be	1FM9	Fluorescent, one 9 W quad, 2 pin, electromagnetic NPF ballast
ordered from d'ac.	1FM13	Fluorescent, one 13 W quad, 2 pin, electromagnetic NPF ballast

Voltage	<b>120</b> 120V	<b>277</b> 277V			
Finishes	WH White Gloss bakes	d enamel MB M	atte Black baked enamel		
Options	HPF High power factor electromagnetic ballast				
Faceplate finish options: See Page d9000 for color renderings	MG Metallic Grey BZ Metallic Bronze GM Metallic Green RD Metallic Red	<ul><li>AN Metallic Anthracite</li><li>BC Black Crinkle</li><li>T1 Light Tan</li><li>SF Seafoam</li></ul>	<ul><li>BG Black Gloss</li><li>CU Metallic Copper</li><li>T2 Medium Tan</li><li>BL Metallic Blue</li></ul>		
	VI. Bright Yellow	RB Bright Red	MP Magenta Pink		


**G2** Medium Grey

**Special Orders**For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.

SCF Special Finish-must supply paint chip

Light Grey

G1



## How to specify

Work space	ce for submitts	als			
Item #	Lamping	Voltage	Faceplate	Options	Sp. Orders