

RNH-HKF design



d5020-1FS23-120-WH-CL

d5020-1FS23-120-WH-CL  
(d5021-1FS23-120-WH-CL)

RNH-HKF design



Item #	Lamping	Voltage	Metal Finish	Shade Color	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

**How to specify**

Example from illustration at left

<b>d5020</b>	<b>-1FS23</b>	<b>-120</b>	<b>-WH</b>	<b>-CL</b>	<input type="text"/>	<input type="text"/>
--------------	---------------	-------------	------------	------------	----------------------	----------------------

**Item Number** d5020 12" diam. LEXY pendant  
d5021 16" diam. LEXY pendant

**Construction** Acrylic prismatic shade. 5" diam. steel canopy. Aluminum components. White, three conductor hanging cord. For standard ceiling junction box mounting. UL listed, cUL certified for dry locations.

**Lamping / Wattage** 1N150 Incandescent, one 150 W, medium base, A type  
*Fixtures supplied less lamps. Lamps may be ordered from d'ac.*  
 1F13 Fluorescent, one 13 W quad, 4 pin, electronic HPF ballast  
 1F18 Fluorescent, one 18 W quad, 4 pin, electronic HPF ballast  
 1FS23 Fluorescent, one 23 W, medium base, triple tube compact  
 1F26 Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast  
 1F32 Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast  
 1F42 Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast  
 1M70\* Metal Halide, one 70 W, medium base, ED-17 type  
 1M100\* Metal Halide, one 100 W, medium base, ED-17 type  
 1M150\* Metal Halide, one 150 W, medium base, ED-17 type  
 \*Remote "F-can" magnetic metal halide ballasts not to exceed 10 feet from lamp; items must use bottom lens (see below)

**Voltage** 120 120V 277 277V

**Finishes** See Page d9000 for color renderings

<b>AL</b> Brushed Aluminum	<b>PA</b> Polished Aluminum	<b>Baked Enamels:</b>
<b>WH</b> White Gloss	<b>G1</b> Light Grey	<b>G2</b> Medium Grey
<b>MG</b> Metallic Grey	<b>AN</b> Metallic Anthracite	<b>BG</b> Black Gloss
<b>MB</b> Matte Black	<b>BC</b> Black Crinkle	<b>CU</b> Metallic Copper
<b>BZ</b> Metallic Bronze	<b>T1</b> Light Tan	<b>T2</b> Medium Tan
<b>GM</b> Metallic Green	<b>SF</b> Seafoam	<b>BL</b> Metallic Blue
<b>RD</b> Metallic Red	<b>RB</b> Bright Red	<b>MP</b> Magenta Pink
<b>YL</b> Bright Yellow	<b>SCF</b> Special Finish—must supply paint chip	

**Standard Shade Colors**

<b>CL</b> Clear	<b>GR</b> Green	<b>BL</b> Blue
<b>MK</b> Milky white	<b>AM</b> Amber	<b>RD</b> Red
<b>PP</b> Pearlescent Pink	<b>PB</b> Pastel Blue	<b>PG</b> Pastel Green
	<b>PW</b> Pastel White	

**Options**

<b>BHC</b> Black, three conductor hanging cord	<b>STEM</b> Rigid, 1/2" diam. stem
<b>BLF</b> Acrylic bottom lens—flat (clear)	<b>BLD</b> Acrylic bottom lens—dome (clear)
<b>CEQ</b> California Earthquake Swivel—must use rigid stem	
<b>ELTRN</b> Remote electronic metal halide ballast, 120 V (70 W & 100 W only) Not to exceed 12 feet from lamp	

**Special Orders** For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.