



d'ac studio design



d5033



Item #	Lamping	Voltage	Finish	Options	Sp. Orders
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Work space for submittals

How to specify

Example from illustration at left

d5033	-1F32	-120	-AN		
-------	-------	------	-----	--	--

Item Number

d5033

60" CLARETA pendant / d'ac studio design

Construction

Spun aluminum shade. Polished chrome trim and clamps with set screws. White opal acrylic diffuser. 5" diam. black canopy. Adjustable height, aircraft cable supports fixture. 60" overall height. Black, 3 conductor cord. For standard ceiling junction box mounting. UL listed, cUL certified for dry, damp and wet locations.

Lamping / Wattage

Fixtures supplied less lamps.
Lamps may be ordered from d'ac.

1N150	Incandescent, one 150 W, medium base, A type
1H100	Halogen, one 100 W, medium base, double encased, T type
1FS23	Fluorescent, one 23 W, medium base, triple tube compact
1F13	Fluorescent, one 13 W quad, 4 pin, electronic HPF ballast
1F18	Fluorescent, one 18 W quad, 4 pin, electronic HPF ballast
1F26	Fluorescent, one 26 W triple tube, 4 pin, electronic HPF ballast
1F32	Fluorescent, one 32 W triple tube, 4 pin, electronic HPF ballast
1F42	Fluorescent, one 42 W triple tube, 4 pin, electronic HPF ballast
1M70*	Metal halide, one 70 W, medium base, ED-17 type
1M100*	Metal halide, one 100 W, medium base, ED-17 type
1M150*	Metal halide, one 150 W, medium base, ED-17 type

*Remote ballast on metal halide versions not to exceed 15 feet from lamp

Voltage

120 120V 277 277V

Finishes

See Page d9000 for color renderings

AL	Brushed Aluminum	PA	Polished Aluminum	Baked Enamels:	
WH	White Gloss	G1	Light Grey	G2	Medium Grey
MG	Metallic Grey	AN	Metallic Anthracite	BG	Black Gloss
MB	Matte Black	BC	Black Crinkle	CU	Metallic Copper
BZ	Metallic Bronze	T1	Light Tan	T2	Medium Tan
GM	Metallic Green	SF	Seafoam	BL	Metallic Blue
RD	Metallic Red	RB	Bright Red	MP	Magenta Pink
YL	Bright Yellow	SCF	Special Finish—must supply paint chip		

Options

WET - UL listed for wet and damp locations **STEM** Rigid, 1/2" diam. stem (aircraft cable and cord replaced by 1/2" diam. rigid stem and modified canopy)
COIL - Coiled electrical cord. Not an option for metal halide

Special Orders

For modifications to dimensions, electrical requirements and other special orders, please contact your d'ac representative.

