Quick Fix | 2826

Broadloom



Quick Fix | 2826

Broadloom

Colorways



Product Specifications

Construction	Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Nylon Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	26 oz./sy (881 grams/m²)
Pile Density	7,200 oz./sy (267.14 kg/m³)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	11.7 stitches/in (4.61 stitches/cm)
Standard Size	12 ft (3.66 m)
Lifetime Warranties	Protection from Delamination Failure,
	Tuft Bind Strength (edge ravel, yarn pulls,
	zippering), Fiber Performance for Wear,
	Fiber Performance for Static, Colorfastness to
	Light and Atmospheric Contaminants, Stain
	Removal

Environmental Specifications & Tests

	. A	
Sustainable Carpet Assessment Standard NSF Gold		
Indoor Air Quality	GLP 5055	
Total Recycled Content	13%-24%	
Pill Test	Yes	
Flooring Radiant Panel	Class 1	
Smoke Density	Less than 450 flaming (ASTM E 662	
Static Test	Less than 3 kv (AATCC-134)	
Lightfastness	Yes	
ADA Compliance	Compliant For Accessible Routes	

Special Treatments

ProTex® (Soil Release)	Yes
ProSept® (Antimicrobial)	Optional
Stain/Bleach Resistant	Yes

Coordinating Products

Corporate Values Too Problem Solved, Solutions





