



Specifications	Bare Earth	Bare Earth
Style Number	8BH200630R	8BH200630R
Product Construction	Woven	Woven
Fiber	Aquafil® Alto cf nylon	Aquafil® Alto cf nylon
Dye Method	Piece Dye	Piece Dye
Soil/Stain Protection	Protekt®	Protekt®
Antimicrobial	Intersept®	Intersept®
Secondary Backing	High PerformancePC™	
Yarn Weight	20 oz/yd²	678 g/m²
Machine Gauge		
Pile Height		
-High	.05 in	1.3 mm
-Medium		
-Low	.024 in	.6 mm
Stitches:	10 /in	39.37 ends/10 cm
Pile Density	4860	
Total Thickness	.135	3.429
Size	12 ft 6 in	3.810 m
Pattern Repeat	None	
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static	(AATCC - 134) < 3.5 KV	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Prestige PlusRC 100™,High PerformancePC™	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.