



<b>Specifications</b>	<b>Milford Sound</b>	<b>Milford Sound</b>
Style Number	4MS3606200	4MS3606200
Product Construction	Tufted Level Loop	Tufted Level Loop
Fiber	100% New Zealand wool	100% New Zealand wool
Dye Method	Yarn Dye	Yarn Dye
Soil/Stain Protection		
Antimicrobial		
Secondary Backing	Action-Bac	
Yarn Weight	36 oz/yd <sup>2</sup>	1221 g/m <sup>2</sup>
Machine Gauge	5/32 in	25.2 ends/10 cm
Pile Height		
-High	.235 in	6 mm
-Medium		
-Low		
Stitches:	10.5 /in	41.3385 ends/10 cm
Pile Density	4595	
Total Thickness	.3	7.62
Size	12 ft	3.657 m
Pattern Repeat	15/32 in (w) stripe	1.1908 cm (w) stripe
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static		
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Action-Bac,Optimum BarrierRC™,Prestige PlusRC™	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.