



Specifications	Shearling Suede	Shearling Suede
Style Number	8SJ6506400	8SJ6506400
Product Construction	Woven Cut Pile	Woven Cut Pile
Fiber	100% Wool	100% Wool
Dye Method	Yarn Dye	Yarn Dye
Soil/Stain Protection		
Antimicrobial		
Secondary Backing	Synthetic	
Yarn Weight	65 oz/yd ²	2204 g/m ²
Machine Gauge		
Pile Height		
-High		
-Medium		
-Low		
Stitches:	0 /in	0 ends/10 cm
Pile Density	6324	
Total Thickness	.56	14.224
Size	12 ft 10 in	3.911 m
Pattern Repeat	1-3/4 in W Stripe	3.290 cm W Stripe
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static		
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Synthetic	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.