



Specifications	Social Network	Social Network
Style Number	8SO320630R	8SO320630R
Product Construction	Tufted Tip-Sheared	Tufted Tip-Sheared
Fiber	Antron® Legacy of Nylon // Antron® Legacy HRC of nylon	Antron® Legacy of Nylon // Antron® Legacy HRC of nylon
Dye Method	Piece Dye	Piece Dye
Soil/Stain Protection	Protekt®	Protekt®
Antimicrobial	Intersept®	Intersept®
Secondary Backing	High PerformancePC™	
Yarn Weight	32 oz/yd²	1085 g/m²
Machine Gauge	5/64 in	50.4 ends/10 cm
Pile Height		
-High	.248 in	6.3 mm
-Medium	.172 in	4.4 mm
-Low	.102 in	2.6 mm
Stitches:	13.7 /in	53.9369 ends/10 cm
Pile Density	6620	
Total Thickness	.309	7.8486
Size	12 ft 6 in	3.810 m
Pattern Repeat	18-3/4 in (w) x 18-3/4 in (l)	47.6250 cm (w) x 47.6250 cm (l)
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static	(AATCC - 134) < 3.5 KV	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Prestige PlusRC™,Optimum BarrierRC™,Optimum BarrierRC™ Cushion,High PerformancePC™,NexStep™ Cushion Tile	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.