
BENTLEY PRINCE STREET



Specifications	Twist & Shout Loop	Twist & Shout Loop
Style Number	8KTSL06400	8KTSL06400
Product Construction	Tufted Level Loop	Tufted Level Loop
Fiber	Branded 100% Type 6 Nylon	Branded 100% Type 6 Nylon
Dye Method	Other	Other
Soil/Stain Protection	Weave Guard	Weave Guard
Antimicrobial		
Secondary Backing	Dimensionally Stable Weave Back	
Yarn Weight	30 oz/yd²	1017 g/m²
Machine Gauge	1/10 in	39.4 ends/10 cm
Pile Height		
-High	.236 in	6 mm
-Medium -Low		
Stitches:	0 /in	0 ends/10 cm
Pile Density	6433	
Total Thickness		
Size	13 ft 2 in	4.013 m
Pattern Repeat	51-27/64 in W x 31-3/32 in L	130.6115 cm W x 78.9781 cm L
Radiant Panel		
Smoke Density		
Static		
Flammability		
Backing Options	Dimensionally Stable Weave Back	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made is USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.

14641 East Don Julian Road City of Industry, California 91746

www.bentleyprincestreet.com