



Specifications	Vestito	Vestito
Style Number	8VV440630R	8VV440630R
Product Construction	Tufted Cut & Loop	Tufted Cut & Loop
Fiber	Ultron® Color nylon 6,6 by Solutia	Ultron® Color nylon 6,6 by Solutia
Dye Method	Piece Dye	Piece Dye
Soil/Stain Protection	Protekt®	Protekt®
Antimicrobial	Intersept®	Intersept®
Secondary Backing	High PerformancePC™	
Yarn Weight	44 oz/yd ²	1492 g/m ²
Machine Gauge	5/64 in	50.4 ends/10 cm
Pile Height		
-High	.268 in	6.8 mm
-Medium		
-Low	.214 in	5.4 mm
Stitches:	8.5 /in	33.4645 ends/10 cm
Pile Density	7632	
Total Thickness	.365	9.271
Size	12 ft 6 in	3.810 m
Pattern Repeat	18-3/4 in W x 37-1/2 in L	47.6250 cm W x 95.2500 cm L
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static	(AATCC - 134) < 3.5 KV	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	Prestige PlusRC™,High PerformancePC™,Optimum BarrierRC™,Optimum BarrierRC™ Cushion	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.