



Specifications	Vivid Ombre	Vivid Ombre
Style Number	8VI240630R	8VI240630R
Product Construction	Tufted Textured Loop	Tufted Textured Loop
Fiber	Antron Lumena® solution dyed cf nylon	Antron Lumena® solution dyed cf nylon
Dye Method	Solution Dye	Solution Dye
Soil/Stain Protection	Protekt®	Protekt®
Antimicrobial	Intersept®	Intersept®
Secondary Backing	High PerformancePC™	
Yarn Weight	24 oz/yd ²	814 g/m ²
Machine Gauge	5/64 in	50.4 ends/10 cm
Pile Height		
-High	.239 in	6.1 mm
-Medium	.186 in	4.7 mm
-Low	.076 in	1.9 mm
Stitches:	11.2 /in	44.0944 ends/10 cm
Pile Density	7170	
Total Thickness	.28	7.112
Size	12 ft 6 in	3.810 m
Pattern Repeat	18-3/4 in W x 68-3/4 in L	47.6250 cm W x 174.6250 cm L
Radiant Panel	Passes Class 1 (ASTM E-648) Critical Radiant Flux	
Smoke Density	Dm corrected	
Static	(AATCC - 134) < 3.5 KV	
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)	
Backing Options	High PerformancePC™,Prestige PlusRC™,Optimum Barrier™ II,Optimum BarrierRC™ II Cushion,NexStep® Cushion Tile	

Please inquire about product warranties for specific backing options. Patterned carpet may require special attention by the installer to assure a suitable match, and must be addressed in the original labor quotation. The shearing process may result in a small loss of yarn weight.

Product specifications are subject to normal manufacturing tolerances and may be changed without notice provided performance is not adversely affected. Slight variations in color among different production lots are normal and should be considered in the overall installation plan. Products are covered by manufacturer's written warranty only. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose, are hereby disclaimed. Contact your sales representative for written warranty information. Made in USA. Warning: Unauthorized reproduction of this carpet design constitutes copyright infringement. © 2007 Bentley Prince Street, Inc.