

suretread™ and pavers™

Sizes

6" x 6"
15.2 cm x 15.2 cm
3/8" thick
Square feet per carton: 11



Application

	Residential	Light Commercial	Commercial
Floors	X	X	X
Walls	X	X	X
Counters	X	X	X
Backsplashes	X	X	X

Recommended for interior and exteriors use on residential and commercial floors and walls. Also recommended for industrial applications requiring high compressive strength. Consult your Daltile representative for appropriate application requirements.

Test Results

	ASTM #	Results
Water Absorption	C373	.5% - .4%
Breaking Strength	C648	>400 lbs
Scratch Hardness	MOH's	7
Chemical Resistance	C650	Resistant
Coefficient of Friction	C1028	Wet: 0.83 Dry: 0.72
Wear Rating	PEI	4
**Abrasive finish tests 0.60+ Wet		

Wear Rating

- 1** Light Residential
- 2** Heavy Residential
- 3** Light Commercial
- 4** Heavy Commercial

PEI represents the classification of the abrasion resistance by using the PEI test method for the “Determination of the Resistance to Surface Abrasion of Glazed Tile” under EN154 European Test Procedure.

Notes The natural beauty of ceramic tile lies in its subtle variation of shades. Manufactured tile may vary from these samples. Manufactured in accordance with ANSI A137.1 standards.


Maintenance Routine maintenance will keep your Suretread and Paver tile looking new for years to come. Clean regularly with a low-alkaline detergent diluted with warm water. No waxes or sealers are recommended for this product.

For more information about Daltile products and services, visit our website at www.daltile.com.


7834 C.F. Hawn Freeway
Dallas, Texas 75217
214-398-1411 800-933-TILE




Red Suretread 0Q81



Gray Suretread 0Q76








Red Paver 0Q84 (Smooth Surface)



Gray Paver 0Q85 (Smooth Surface)

Trim

Type	Number	Size
Bullnose		
	P-1665	6H x 6L
	PC-1665	6H x 6L
Cove Base		
	P-3665	6H x 6L
Cove Corner		
	PCR-L-3665	6H x 6L (out)
	PB-3665	3/4H x 6L (in)



suretread™ and pavers™



Photos feature Sierra tile in Red 0Q81



Suretread™ and Pavers™

Floor Tile

With Suretread, floor safety is nothing to worry about. It's random raised tread pattern "pools" grease and water below the level of foot traffic, providing for excellent traction. Low moisture absorption facilitates maintenance, and makes Suretread highly stain-resistant. Its dense, pressed body makes it durable enough for interior and exterior use perfect for commercial applications. And its earthy colors enrich a variety of designs. For floors that require good look and extra durability and safety.



daltile®