

shaw contract group®

innovation
collection: turn-
key

broadloom specifications

style name	innovation	
style number	50914	
construction	pattern loop	
fiber	eco solution q® nylon	
dye method	75% solution dyed/ 25% yam dyed	
	english	metric

pattern repeat	0.40"w x 1.0"l	10.16 mm w x 25.40 mm l
tufted weight	26.0	881.55 g/m²
gauge	1/10	39.37 per 10cm
stitches per inch	12.0	47.24 per 10cm
finished pile thickness	0.143	3.63 mm
total thickness	0.293	7.44 mm
average density	6545	242.69 kg/m³
product size	12 foot	3.66 m
primary backing	synthetic	
secondary backing	classcbac®	
protective treatments	ssp® shaw soil protection	

testing

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

warranties

10 year commercial limited

installation method

direct glue

coordinating products

blog, blog classcbac®, culture, digital, divide, edit, equal, evolution, fossil, global, mecca, metro, space, terra, text, text classcbac®, venture capital

environmental certification

green label plus certification number glp 8472



Specifications are subject to nominal manufacturing variances.
Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429