

**shaw contract group®**

vivid float tile  
collection: dressed to  
kill

**tile specifications**

style name	vivid float tile	
style number	59507	
construction	multi-level pattern loop	
fiber	eco solution q@nylon	
dye method	76% yam dyed / 24% solution dyed	
	english	metric
	-----	
pattern repeat	none	
tufted weight	28.0	949.36 g/m <sup>2</sup>
gauge	1/12	47.24 per 10cm
stitches per inch	10.0	39.37 per 10cm
finished pile thickness	0.160	4.06 mm
total thickness	0.325	8.26 mm
average density	6300	233.60 kg/m <sup>3</sup>
product size	24" x 24"	60.96 cm x 60.96 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments	ssp® shaw soil protection	


**testing**

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

**warranties**

lifetime commercial limited

**installation method**



**coordinating products**

bloom plush, bloom tile, float plush, float tile, paparazzi v2 tile, shadow plush, shadow tile, swirl plush, swirl tile, tailored tile, vivid bloom tile, vivid shadow tile, vivid swirl tile

**environmental certification**

green label plus certification number glp 9968  
nsf140 platinum  
cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.  
Material supply and/or manufacturing processes may necessitate changes without notice.  
shawcontractgroup.com | 1 800.257.7429