

shaw contract group®

vivid shadow tile
collection: dressed to

kill

tile specifications

style name	vivid shadow tile	
style number	59506	
construction	multi-level pattern loop	
fiber	eco solution q® nylon	
dye method	76% yam dyed / 24% solution dyed	
	english	metric

pattern repeat	none	
tufted weight	28.0	949.36 g/m²
gauge	1/12	47.24 per 10cm
stitches per inch	10.0	39.37 per 10cm
finished pile thickness	0.160	4.06 mm
total thickness	0.325	8.26 mm
average density	6300	233.60 kg/m³
product size	24" x 24"	60.96 cm x 60.96 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments	ssp® shaw soil protection	


testing

radiant panel	class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

warranties

lifetime commercial limited

installation method



coordinating products

bloom plush, bloom tile, float plush, float tile, paparazzi v2 tile, shadow plush, shadow tile, swirl plush, swirl tile, tailored tile, vivid bloom tile, vivid float tile, vivid swirl tile

environmental certification

green label plus certification number glp 9968
nsf140 platinum
cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.
Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429