

HOUSING

Dimensions	Length	Width	Height	Cutout
Standard Housing	23"	20-15/16"	8"	14-1/8"

13" Icetron® Induction 1-100/150

Wide beam distribution for general lighting in large spaces from a single horizontally mounted inductively coupled electrodeless lamp. Average lamp life of 100,000 hours makes this fixture ideal for areas where lamp replacement is difficult or costly. Plaster frame lip adjusts to accommodate ceilings up to 2" thick.



HOUSING

QD13=13" Horizontal Induction Downlight

LAMP

1035=(1) 100W 3500°K Induction
1041=(1) 100W 4100°K Induction
1535=(1) 150W 3500°K Induction
1541=(1) 150W 4100°K Induction


BALLAST

E=120 - 277V 50/60 Hz Electronic

ACCESSORIES

HB26=C Channel Bar Hanger, 26" Long, Pair
HB50=C Channel Bar Hanger, 50" Long, Pair
FK5=Field Installed Fuse Kit, 5 Amp

TRIM



TRIM

1301=Open Splay, Self Flanged


FINISH

LI=Low Iridescent Clear
W=Gloss White
BB=Black Baffle
WB=White Baffle

OPTIONS

WF=White Painted Flange (Self Flanged only)

Open Splay



TRIM

1351=Cross Blade, Self Flanged

FINISH

LI=Low Iridescent Clear
W=Gloss White


LENS

(Blank)=No Lens, Open
1G=Prismatic Glass
2G=Diffuse Glass
3G=Clear Glass

OPTIONS

WF=White Painted Flange (Self Flanged only)

Cross Blade



TRIM

1381=Lens, Self Flanged

FINISH

LI=Low Iridescent Clear
W=Gloss White
BB=Black Baffle
WB=White Baffle

LENS

1G=Prismatic Glass
2G=Diffuse Glass
3G=Clear Glass

OPTIONS

WF=White Painted Flange (Self Flanged only)

Lens Downlight



Ordering Example

Housing, Trim, Accessories and Lamps ordered as separate line items.

Housing/Lamp/Ballast	Trim	Accessories
QD131035E	1351LI	HB26