shaw contract group®

distressed oak

hardwood specifications

style	distressed oak	CA244
color	charcoal	00506
color variation	medium
description	5" painted and distressed oak
species	red oak
grain variation	medium
edge profile	beveled
gloss/sheen	low
construction	5-ply engineered with all hardwood core
finish	shaw commercial-grade aluminum oxide

	english	**metric**
width	5"	127.00 mm
total thickness	1/2"	12.70 mm
wear layer thickness	.0984"	2.50 mm
length	8 to 42 "	203 to 1066 mm
packaging	22.00 sq ft per ctn.	2.044 sq m per ctn.

testing

hardness (psi)	1610
radiant panel	Class I

warranties

10 year limited commercial

lifetime commercial

environmental

cradle to cradle silver certified

greenguard certified for children and schools

lacey act compliant - north american species

made in USA

fsc certified material available via special order

installation

grade	suitable for all grade levels
method	glue, nail, float

sundries

glue	shaw urethane adhesive
nail	n/a
float	silent step utlra and shaw tongue and grove adhesive

trims

flush reducer CA928

flush stairnose CA931

quarter round CA927

t-molding CA934

overlap reducer CA929

overlap & stairnose CA932

end molding carpet reducer CA933

wall base CA935

base shoe CA925

square nose CA930

Shaw

Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429

Web2PDF
converted by Web2PDFConvert.com