jolie atelier

Sanitas Wallcoverings are manufactured by: **RJF International Corporation** 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET Pattern Name: Pampa Stripe

OUIK SPEC METRIC UNITS: U.S. UNITS:

QUIK BI EC	0.0. 011110.	METRIC CIVITS.	
Total Weight:	21 oz. PLY	651 g. PLM	
	14 oz. PSY	475 g. PSM	
Roll Width:	52/54 in.	132/137 cm.	
Gauge (average):	0.019 in.	0.48 mm.	
Fabric:	Osnaburg		
Tensile (minimum):	50 x 55 lb _f	222 x 245 N	
Tear (minimum):	25 x 25		
Federal Spec:	CCC-W-408A, Type II		
CFFA Spec:	CFFA-W-101D, Type II		
Fire Testing:	NFPA 101 [®] Life Safety Code [®]		
	NFPA 255 (UL723, CAN S102M) Tunnel Test ¹		
	- Class A Rating		
	NFPA 286 Corner Burn Test ²		
	Meets requirements for Flame Spread, Smoke Developed		
	and Flashover		
	U.L. Listed and Labeled		
Repeat: Horizontal	4.50 in.	11.4 cm	
Vertical	N/A		
Nominal Pattern Width:	52"		
Hanging Instructions:	Reverse – Match Stripes		
1. When tested on GR	C board with A-848-B adhesive	-	
2 When tested on 5/8	" type Y averym board with A 818 B	? adhasiya	

When tested on 5/8" type X gypsum board with A-848-B adhesive

COLORLINE 7 Colorways

Description: A textural cross hatch design with a printed 2 5/8" stripe, alternating negative 1 5/8" space.

JM07-84 Spring Linen	JM07-37 Tussah Silk	JM07-29 Organza
JM07-59 Tapestry Gold	JM07-64 Filaments	Note: Can be cut to narrower
JM07-81 Pongee	JM07-82 Gossamer	width.

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.