

Koroseal Wallcoverings®  
 A Division of RJF International Corporation  
 3875 Embassy Parkway  
 Fairlawn, OH 44333

KOROSEAL WALLCOVERINGS®  
 FACT SHEET  
 Pattern Name: ALTO®

QUICK SPEC	U.S. UNITS	METRIC UNITS
Total Weight	15.0 oz./ linear yard	465 g./ linear meter
	10.0 oz./square yard	339 g./square meter
Roll Width	53/54 in.	135/137 cm.
Thickness	0.0067 in.	0.17 mm.
Fabric: Sheeting	Federal Spec: CCC-W-408A, Type I	CFFA Spec: CFFA-W-101C Type I, Class A
Fire Testing	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E84, CAN S102M) Tunnel Test <sup>1</sup> : Class A Rating	U.L. Labeled and Listed
	NFPA 286 Corner Burn Test <sup>2</sup> : Meets requirements for Flame spread smoke developed and flashover	
Repeat	Vertical: N/A	Horizontal: N/A
1. When tested on GRC board with A-848-B adhesive	2. When tested on 5/8" type-x gypsum board with A-848-B adhesive	

**COLORLINE** **PATTERN NUMBER/NAME OF COLORS**

DESCRIPTION OF THE PATTERN: A lightweight version of our classic Viewpoint pattern.

Available in 6 colorways.

HANGING INSTRUCTIONS: Match: Random Match Reverse Strips: Yes

SPECIAL INSTRUCTIONS (if any):

V215-16

V215-28

V215-30

V215-31

V215-33

V215-41