

Classic, beautiful and durable enough to stand up to rough treatment. This illusion of natural woven cane or “Earth Fibers” illustrates Maya’s devotion to capturing depth and texture.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 474 g PSM
Roll Width	54 in.	137 cm
Gauge	28 Mils	0.71 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 10 Colorways

- | | |
|---------------------|--------------------|
| PA21-15 Aruba | PA21-27 Moorea |
| PA21-36 Belize | PA21-18 Roseau |
| PA21-07 Dominica | PA21-50 St. John’s |
| PA21-10 Martinique | PA21-61 St. Lucia |
| PA21-23 Montego Bay | PA21-39 Trinidad |