

# First Appearances®

## P/4043 CleanSweep

<b>Construction</b>	Tufted, Cut Pile
<b>Face Fiber</b>	100% Milliken-Certified WearOn® Type 6,6 Nylon Twisted and Heat Set for Maximum Performance
<b>Antimicrobial Dye Method</b>	AlphaSan® Built-In Protection Millitron®
<b>Finished Face Weight</b>	26 oz./sq.yd. (881.6 g./sq.m.)
<b>Gauge</b>	5/32 (25.2/10 cm.)
<b>Rows</b>	5.6/in. (22.0/10 cm.)
<b>Tufts</b>	35.8/sq.in. (554.4/100 sq.cm.)
<b>Finished Pile Height</b>	0.22 in. (5.6 mm.) avg.
<b>Density Factor</b>	704,640
<b>Average Density</b>	4,255
<b>Standard Backing</b>	PVC-Free EverWher® Plus ES hardback
<b>Recycled Content by Total Product Weight</b>	20% Pre-Consumer, 6% Post-Consumer
<b>Nominal Total Thickness</b>	0.435 in. (11.0 mm.)
<b>Tile Size</b>	50cm x 50cm (19.7 x 19.7 in.)
<b>Quantity per carton</b>	16 tiles (4 sq.m. or 4.784 sq.yds.)
<b>Nominal Total Weight</b>	117.6 oz./sq.yd. (3,987.5 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450
<b>Methenamine Pill Test (CPSF FF-1-70 or ASTM D 2859)</b>	Self-Extinguishing
<b>Lightfastness (AATCC 16E)</b>	≥ 4.0 at 80 hrs.
<b>Crocking (AATCC 165)</b>	≥ 4.0 wet or dry
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV, Permanent Conductive Fiber
<b>Dimensional Stability - Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Appearance Retention Rating (CRI TM101)</b>	Heavy Use
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality – CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



### Warranties:

Five-Year Face Fiber Wear  
Lifetime Antimicrobial Protection (AlphaSan®)  
Lifetime Antistatic  
Lifetime Color Pattern Permanency  
Lifetime Cushion Resiliency  
Lifetime Delamination of Backing  
Lifetime Dimensional Stability

Lifetime Edge Ravel  
Lifetime Floor Compatibility  
Lifetime Floor Release  
Lifetime Moisture Resistance  
Lifetime Tuft Bind  
Flammability