jolie atelier

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET Pattern Name: Cannes

QUIK SPEC U.S. UNITS: METRIC UNITS:

QCIII DI LC	C.S. CIVIIS.	THE THE CITIES.	
Total Weight:	21 oz. PLY	651 g. PLM	
	14 oz. PSY	475 g. PSM	
Roll Width:	52/54 in.	132/137 cm.	
Gauge (average):	0.024 in.	0.61 mm.	
Fabric:	Osnaburg		
Tensile (minimum):	50 x 55 lb _f	222 x 245 N	
Tear (minimum):	25 x 25		
Federal Spec:	CCC-W-408A, Type II		
CFFA Spec:	CFFA-W-101D, Type II		
Fire Testing:	NFPA 101 [®] Life Safety Code [®]		
	NFPA 255 (UL723, CAN S102M) Tunnel Test ¹		
	- Class A Rating NFPA 286 Corner Burn Test ²		
	Meets requirements for Flame Spread, Smoke Developed		
	and Flashover		
	U.L. Listed and Labeled		
Repeat:	N/A		
Nominal Pattern Width:	52"		
Hanging Instructions:	Reverse – Random		
1. When tested on G	RC board with A-848-B adhesive		
2. When tested on 5/	8" type X gypsum board with A-848-B	3 adhesive	

COLORLINE 9 Colorways

Pattern Description: Elegant fabric emboss, classic design.

JM14-85 Oxford Green	JM14-89 Dry Goods	JM14-29 Hopsack
JM14-20 Spring Linen	JM14-33 Greige	JM14-47 Raw
JM14-07 Fine Gauze	JM14-24 Weaver's Cloth	JM14-10 Silken Threads
Note: Can be split to 27"		

<u>Notes:</u>

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.