

Warwick offers a colorful alternative to stipples and can be used in large and small areas without overwhelming its surroundings.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 474.4 g PSM
Roll Width	53/55 in.	134/139 cm
Gauge	22 Mils	0.56 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical	N/A
	Horizontal	N/A
	Match Information	Random Match, Reverse Hang
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 8 Colorways

M620-01
M620-07
M620-14
M620-25
M620-30
M620-39
M620-51
M620-74