

A subtle pattern and coloration that move with the light. Inlay feels like a dye-cut grasscloth in a material strong enough for the highest traffic areas.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 474 g PSM
Roll Width	53/55 in.	134/140 cm
Gauge	22 Mils	0.56 mm
Fabric	Non-Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical	8 in. 20.32 cm
	Horizontal	8 in. 20.32 cm
	Match Information	Straight Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 11 Colorways

- | | |
|-----------------------|-----------------------|
| IN21-54 Cabernet | IN21-17 Linen |
| IN21-34 Champagne | IN21-05 Natural Linen |
| IN21-49 Desert Paint | IN21-38 Natural Silk |
| *IN21-29 Golden Cloth | IN21-12 Spring Wheat |
| IN21-57 Golden Copper | IN21-43 Vanilla Bean |
| IN21-84 Green Bamboo | |

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing