

Cavollo Stria adds a soft stripe to the richly translucent quality of our crinkled Italian silk pattern Cavollo. Color coordinated to Cavollo, Cavollo Stria becomes the perfect coordinate or can be used on its own.

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	53/54 in.	135/137 cm
Gauge	23 Mils	0.58 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical Horizontal Match Information	N/A 1.5 in. Horizontal Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 5 Colorways

- MS20-06
- MS20-19
- MS20-27
- MS20-48
- MS20-57