jolie atelier

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: Anouschka

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
-----------	-------------	----------------------

QCIII DI LIC	e.s. e1(115)	THE THE CITIES.	
Total Weight:	21 oz. PLY	651 g. PLM	
	14 oz. PSY	475 g. PSM	
Roll Width:	55/56 in.	139/142 cm.	
Gauge (average):	0.022 in.	0.56 mm.	
Fabric:	Non-woven		
Tensile (minimum):	50 x 55 lb _f	222 x 245 N	
Tear (minimum):	25 x 25		
Federal Spec:	CCC-W-408A, Type II		
CFFA Spec:	CFFA-W-101D, Type II		
Fire Testing:	NFPA 101 [®] Life Safety Code [®]		
	NFPA 255 (UL723, CAN S102M) Tunnel Test ¹		
	- Class A Rating		
	NFPA 286 Corner Burn Test ²		
	Meets requirements for Flame Spread, Smoke Developed		
	and Flashover	•	
	U.L. Listed and Labeled		
Repeat: Horizontal	17.75 in.	45.0 cm	
Vertical	22.25 in.	56.5 cm	
Nominal Pattern Width:	54"		
Hanging Instructions:	Non-Reverse – Straight Match		
1. When tested on G	RC board with A-848-B adhesive		
2 When tested on 5/	9" tong V gungum board with A 949 D	adhagina	

2. When tested on 5/8" type X gypsum board with A-848-B adhesive

COLORLINE 8 Colorways

Pattern Description: Soft diffused twig or field stalk, understated and useable for all market segments.

,				
JM18-45 Smokey Topaz	JM18-33 Amber	JM18-86 Whispers		
JM18-61 Purple Haze	JM18-17 Toffee	JM18-82 Mirage		
JM18-30 Golden Mist	JM18-29 Soft Cashmere	Note: Cannot be split to 27."		

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.