



Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified WearOn® Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Dye Method	Millitron®
Gauge	1/10 (39.4/10 cm.)
Rows	14.4/in. (56.7/10 cm.)
Tufts	144.0/sq.in. (2,234.0/100 sq.cm.)
Density Factor	197,121
Standard Backing	PVC-Free Underscore™ ES cushion
	Available with TractionBack®
	Available with ESP cushion for NSF 140 Platinum certification
Recycled Content by Total Product Weight	ES Backing: 31.7% Pre-Consumer
	ESP Backing: 20.8% Pre-Consumer, 11% Post-Consumer
	0.27 in. (6.9 mm.) avg.
Nominal Total Thickness	
Tile Size	1m x 1m (39.4 x 39.4 in.)
Nominal Total Weight	89.0 oz./sq.yd. (3,017.8 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 hrs.
Crocking (AATCC 165)	≥ 4.0 wet or dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Dimensional Stability - Aachener Test (DIN Std 54318)	≤ 0.2%
Texture Appearance Retention Rating (TARR)	Severe Traffic End-Use Applications
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality - CRI Green Label Plus™	GLP0793, Carpet Category 5Y

Design Copyright - Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Warranties:

Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Antistatic
Lifetime Color Pattern Permanency
Lifetime Cushion Resiliency
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Edge Ravel

Lifetime Face Fiber Wear
Lifetime Floor Compatibility
Lifetime Floor Release
Lifetime Moisture Resistance
Lifetime Staining/Soiling (StainSmart®)
Lifetime Tuft Bind
Flammability