

These magical, crinkled stripes play with the light in the most remarkable way- shifting from matte to shiny as their mood changes. Sensually rich, elegantly lush, the sun-infused surfaces appear in metallics, pearlized or iridescents giving Pavillion the appearance of being patinaed with age.

	US UNITS	METRIC UNITS
Total Weight	26.0 oz PLY 17.3 oz PSY	806 g PLM 587.6 g PSM
Roll Width	54 in.	137 cm
Gauge	27 Mils	0.68 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25	
Federal Spec	CCC-W-408A, Type II	
CFFA Spec	CFFA-W-101-D, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed	
Repeat	Vertical Horizontal Match Information	N/A N/A Straight Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 15 Colorways

- | | | |
|-----------------------|----------------------|--------------------|
| PV26-19 Beige | PV26-89 Herbal Green | PV26-77 Ripple |
| PV26-12 Blanco | PV26-59 Mahogany | PV26-72 Royale |
| PV26-01 Bone White | PV26-56 Penny Copper | PV26-93 Slate |
| PV26-51 Filigree Gold | PV26-98 Pewter | PV26-43 Taupe |
| PV26-39 Golden Glow | PV26-82 Rainforest | PV26-05 White Sand |

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing.