

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: Strawline©

QUIK SPEC	U.S. UNITS:	METRIC UNITS:		
Total Weight:	21 oz. PLY	651 g. PLM		
	14 oz. PSY	475 g. PSM		
Roll Width:	52/54 in.	132/137 cm.		
Gauge (average):	0.025 in.	0.64 mm.		
Fabric:	Osnaburg			
Tensile (minimum):	50 x 55 lb _f	222 x 245 N		
Tear (minimum):	25 x 25			
Federal Spec:	CCC-W-408A, Type II			
CFFA Spec:	CFFA-W-101D, Type II			
Fire Testing:	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹			
	- Class A Rating			
	NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed			
	and Flashover			
	U.L. Listed and Labeled			
Nominal Pattern Width:	51in.	130 cm.		
Hanging Instructions:	Random Reverse			
 When tested on GI 	RC board with A-848-B adhesive			
2. When tested on 5/8	8" type X gypsum board with A-848-B	adhesive		

COLORLINE 16 Colorways

Pattern Description: Great straw emboss – a natural linear texture useable for all market segments.

5L21-33 Gossling	5L21-02 Hourglass	5L21-37 Gold Rush	5L21-21 Magical Mist
5L21-94 Charcoal	5L21-26 Corn Silk	5L21-09 Stepping Stone	5L21-71 Lacewing
5L21-77 Dewdrop	5L21-28 Camel's Back	5L21-12 Caramel	5L21-17 Woodbury
5L21-83 Field Grass	5L21-80 Leprechaun	5L21-52 Rustico	5L21-87 Pine Cone

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.