

Intervals®

P/6619 Fret Not

Construction	Tufted, Textured Loop Pile
Face Fiber	100% Milliken-Certified WearOn® Type 6,6 Nylon
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® Built-In Protection
Dye Method	DCP (Digital Color Placement)
Finished Face Weight	27 oz./sq.yd. (915.5 g./sq.m.)
Gauge	1/10 (39.4/10 cm.)
Rows	12.2/in. (48.0/10 cm.)
Tufts	122.0/sq.in. (1,891.2/100 sq.cm.)
Finished Pile Height	0.13 in. (3.3 mm.) avg.
Density Factor	403,249
Average Density	7,477
Standard Backing	PVC-Free Comfort Plus® ES cushion Available with TractionBack® Available with ESP cushion for NSF 140 Platinum certification With ESP Backing: 22% Pre-Consumer, 3% Post-Consumer With ESP Backing: 14% Pre-Consumer, 11% Post-Consumer
Recycled Content by Total Product Weight	
Nominal Total Thickness	0.41 in. (10.41 mm.)
Tile Size	50cm x 50cm (19.7 x 19.7 in.) 1m x 1m (39.4 x 39.4 in.)
Nominal Total Weight	109.7 oz./sq.yd. (3,719.6 g./sq.m.)
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 hrs.
Crocking (AATCC 165)	≥ 4.0 wet or dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Dimensional Stability - Aachener Test (DIN Std 54318)	≤ 0.2%
Appearance Retention Rating (CRI TM101)	Severe Use
Recommended Maintenance	MilliCare® Textile and Carpet Care Service Network
Indoor Air Quality – CRI Green Label Plus™	GLP0793, Carpet Category 5Y

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



Warranties:

Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Antistatic
Lifetime Color Pattern Permanency
Lifetime Cushion Resiliency
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Edge Ravel

Lifetime Face Fiber Wear
Lifetime Floor Compatibility
Lifetime Floor Release
Lifetime Moisture Resistance
Lifetime Staining/Soiling (StainSmart®)
Lifetime Tuft Bind
Flammability



Milliken Contract

