

Vicrtex Wallcoverings®
 A Division of RJF International Corporation
 3875 Embassy Parkway
 Fairlawn, OH 44333

VICRTEX
 FACT SHEET
 Pattern Name: BRUNSWICK®

QUIK SPEC	U.S. UNITS	METRIC UNITS
Total Weight	15.0 oz./ linear yard	465 g./ linear meter
	10.0 oz./square yard	339 g./square meter
Roll Width	53/54 in.	135/137 cm.
Thickness	0.0067 in.	0.17 mm.
Fabric: Sheeting	Federal Spec: CCC-W-408A, Type I	CFFA Spec: CFFA-W-101C Type I, Class A
Fire Testing	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E84, CAN S102M) Tunnel Test ¹ : Class A Rating	U.L. Labeled and Listed
	NFPA 286 Corner Burn Test ² : Meets requirements for Flame spread smoke developed and flashover	
Repeat	Vertical: N/A	Horizontal: N/A
1. When tested on GRC board with A-848-B adhesive	2. When tested on 5/8" type-x gypsum board with A-848-B adhesive	

COLORLINE **PATTERN NUMBER/NAME OF COLORS**

DESCRIPTION OF THE PATTERN: A lightweight version of our classic Lino pattern.

Available in 5 colorways.

HANGING INSTRUCTIONS: Match: Random Match Reverse Strips: Yes

SPECIAL INSTRUCTIONS (if any):

BR15-05

BR15-06

BR15-23

BR15-91

BR15-93