

Borders Collection



- ▶ Vinyl or vinyl coated roll stock available in 2 1/2" (63.5mm) to 26" (660mm) heights and 5 yard (4.57m) lengths
- ▶ More than 500 borders provide a diverse selection to choose from
- ▶ Separated into three categories for easy selection
 - Transitional
 - Traditional
 - Contemporary



IPC.475/REV.4

P.O. Box 406 · Muskego, Wisconsin 53150 USA
inprocorp.com
Nationwide 800.222.5556/Fax 888.715.8407
International Sales 262.679.5521/Fax 262.679.5524

INPRO
IPC Interior Protection Products
and Decorative Surfaces

Borders Collection

Suggested Specifications

PART 1 - GENERAL

1.01 SUMMARY

- A. Decorative wallcovering borders for interior wall surfaces

1.02 SECTION INCLUDES

- A. Antera Wallcovering Borders

1.03 REFERENCES

- A. National Fire Protection Association (NFPA)

1.04 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide Antera Wallcovering Borders that conform to the following requirements of regulatory agencies and the quality control of IPC Door and Wall Protection Systems, InPro Corporation.

- 1. Fire Performance Characteristics: Provide vinyl wallcovering borders conforming to NFPA Class A fire rating.

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each type and pattern of wallcovering border specified.
- B. Detail Drawings: Installation details with the appropriate adhesive for specific project substrate.
- C. Samples: Full width samples not less than 12" (305mm) long, for verification purposes of wallcovering border, of each type and color indicated.
- D. Manufacturer's Installation Instructions: Printed installation instructions for each type of wallcovering border.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite and store in original packaging in a climate controlled location away from direct sunlight.
- B. Inspect materials at delivery to assure that the specified products have been received.
- C. Store in original packaging in a climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

- A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.08 WARRANTY

- A. Standard IPC Limited Warranty against material and manufacturing defects for a period of five years.

PART 2 - PRODUCTS

2.01 MANUFACTURER

- A. Acceptable Manufacturer/Distributor: IPC Door and Wall Protection Systems, InPro Corporation, PO Box 406, Muskego, WI 53150 USA,: Telephone: 800.222.5556, Fax: 888.715.8407, www.inprocorp.com

- B. Substitutions: Not permitted.

- C. Provide all wallcovering borders and wall protection from a single source.

2.02 WALLCOVERING BORDERS

- A. Antera Wallcovering Borders

- 1. Vinyl or vinyl coated roll stock
 - a. Border Height: 2 1/2" (63.5mm) to 26" (660mm)
 - b. Length: 5 yards (4.57m)

- B. Finishes: Colors and patterns of the Antera Wallcovering Borders to be selected by the architect from IPC finish selection. Specify pattern number, pattern name, and pattern color for each wallcovering border selected.

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Examine areas and conditions in which Antera Wallcovering Borders will be installed.
 - 1. Complete all finishing operations, including painting, before beginning installation of Antera Wallcovering Borders.
- B. Wall surface shall be dry and free from dirt, grease and loose paint.

3.02 PREPARATION

- A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

3.03 INSTALLATION

- A. General: Apply adhesive and wallcovering border in accordance with the IPC installation instructions.
- B. Installation of Antera Wallcovering Borders:
 - On painted walls
 - 1. All walls must be clean, smooth, sound and free from dirt and paste residue.
 - 2. Apply wallcovering adhesive to the back of the border.
 - 3. Fold pasted ends together.
 - 4. Book accordion style for 2 minutes.
 - 5. Smooth onto surface with a damp sponge or plastic smoother. Work out any bubbles.
 - 6. Wash applied border to remove paste residue. Over vinyl wallcovering

- 1. All walls must be clean, smooth, sound and free from dirt and paste residue.
- 2. Apply vinyl over vinyl adhesive to the back of the border.
- 3. Fold pasted ends together.
- 4. Book accordion style for 2 minutes.
- 5. Smooth onto surface with a damp sponge or plastic smoother. Work out any bubbles.
- 6. Wash applied border to remove paste residue.

3.04 CLEANING

- A. At completion of the installation, clean surfaces in accordance with the IPC clean-up and maintenance instructions.

