

Lippert® Cultured Marble Shower Receptors (Standard, ADA and Custom)



- ▶ Non-skid textured cultured marble shower receptor helps to prevent slips and falls
- ▶ Integral water barrier prevents water seepage behind or under shower receptor
- ▶ Available in the complete Lippert® Cultured Marble color palette

IPC.748/REV.3



P.O. Box 406 · Muskego, Wisconsin 53150 USA
inprocorp.com
Nationwide 800.222.5556/Fax 888.715.8407
International Sales 262.679.5521/Fax 262.679.5524

INPRO
IPC Interior Protection Products
and Decorative Surfaces

Lippert® Cultured Marble Shower Receptors – Standard, ADA and Custom

Suggested Specifications

PART 1 – GENERAL

1.01 SUMMARY

A. Shower Receptors

1.02 SECTION INCLUDES

A. Cultured marble shower receptors

B. Basins

1.03 REFERENCES

A. American National Standards Institute (ANSI)

1.04 SYSTEM DESCRIPTION

A. Performance Requirements: Provide shower receptors that conform to the following requirements of regulatory agencies and the quality control of InPro Corporation.

1. Provide shower receptors that conform to ANSI Z124.1.2-2005 when tested for workmanship and finish, structural integrity and material characteristics.

1.05 SUBMITTALS

A. Product Data: Manufacturer's printed product data for each type of shower receptors specified.

B. Samples: Verification samples minimum of 3" x 3" samples indicating color and pattern.

D. Manufacturer's Installation Instruction: Printed installation instructions for shower receptors.

1.06 DELIVERY, STORAGE AND HANDLING

A. Deliver materials in unopened factory packaging to the jobsite

B. Inspect materials at delivery to assure that specified products have been received.

C. Store in original packaging in an interior climate controlled location away from direct sunlight.

1.07 PROJECT CONDITIONS

A. Environmental Requirements: Products must be installed in an interior climate controlled environment.

1.08 WARRANTY

A. Standard LIPPERT® Cultured Marble Limited 5 Year Warranty against material and manufacturing defects.

PART 2 – PRODUCTS

2.01 MANUFACTURER

A. Acceptable Manufacturer: InPro Corporation, PO Box 406 Muskego, WI 53150 USA; Telephone: 800-222-5556, Fax: 888-715-8407, inprocorp.com

B. Substitutions: Not permitted

C. Provide all shower receptors from a single source.

2.02 MANUFACTURED UNITS

A. Shower receptors

1. Standard Shower Receptors

a. Receptor Size, Model Number

1. 32" x 32", SR3232, Receptor includes: Chrome drain.
2. 36" x 36", SR3636, Receptor includes: Chrome drain.
3. 32" x 48", SR3248, Receptor includes: Chrome drain.
4. 36" x 48", SR3648, Receptor includes: Chrome drain.
5. 42" x 48", SR4248, Receptor includes: Chrome drain.
7. 32" x 60" offset drain, SR3260(L) or (R), Receptor includes: Chrome drain.
8. 36" x 60", SR3660, Receptor includes: Chrome drain.
9. 36" double threshold, SR36D, Receptor includes: Chrome drain.
10. 36" x 36" Neo-angle Corner, SR36C, Receptor includes: Chrome drain.
11. 42" x 42" Neo-angle Corner, SR42C, Receptor includes: Chrome drain.

Common Features: Receptors shall have a drain slope of 1/4" per foot. Integral water guard barrier shall be 1" high. Front threshold shall be 4 1/2" high.

B. Custom ADA Shower Receptors

1. Center Drain Location: Maximum receptor size shall be 90" deep x 114" wide
Receptor threshold shall be 1/2" high with beveled edges.
Slope to drain shall be 1/4" per foot.

See table below for recess depth:

Recess Depth – Center Drain Location		
Receptor Width to Furthest Edge	Distance from Center of Drain	Receptor Recess Depth
36"	18"	1 1/2"
42"	21"	1 9/16"
48"	24"	1 5/8"
54"	27"	1 11/16"
60"	30"	1 3/4"
66"	33"	1 13/16"
72"	36"	1 7/8"
78"	39"	1 15/16"
84"	42"	2"
90"	45"	2 1/16"
96"	48"	2 1/8"
102"	51"	2 3/16"
108"	54"	2 1/4"
114"	57"	2 5/16"

2. Offset Drain Location (9" from edge): Maximum receptor size shall be 90" deep x 66" wide.

Receptor threshold shall be 1/2" high with beveled edges.

Slope to drain shall be 1/4" per foot.

See table below for recess depth:

Recess Depth – Offset Drain (9" from edge)

Receptor Width to Furthest Edge	Distance from Center of Drain	Receptor Recess Depth
36"	27"	1 11/16"
42"	33"	1 13/16"
48"	39"	1 15/16"
54"	45"	2 1/16"
60"	51"	2 3/16"
66"	57"	2 5/16"

C. Custom Receptors (Non-ADA)

Maximum size shall be 90" x 114",

Slope to drain 1/4" per foot,

Minimum drain location - 9" from inside walls.

Threshold 4 7/8" (4" exposed).

Install receptor 7/8" below finish floor.

2.02 MATERIALS

A. Lippert Cultured Marble: Shower receptors shall be gel-coat and manufactured from polyester resins with natural filler material.

2.03 FINISHES

A. Color and pattern of Lippert Cultured Marble showers and shower receptors to be selected by the architect from the Lippert Cultured Marble finish selection. Surface shall have a gloss, satin or pearl finish.

PART 3 – EXECUTION

3.01 EXAMINATION

A. Examine areas and conditions in which shower receptors will be installed.

3.02 PREPARATION

A. General: Prior to installation, clean area to remove dust, debris and loose particles.

3.03 INSTALLATION

A. General: Install components plumb and level, scribe adjacent finishes, in accordance with approved shop drawings and recommended installation instructions.

3.04 CLEANING

A. At completion of the installation, clean surfaces in accordance with the InPro Decorative Surfaces clean-up and maintenance instructions.

